



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D975XBX2 motherboard (3.73 GHz, Intel(R) Pentium(TM) processor Extreme Edition 965)

SPECint2000 = 1854

SPECint_base2000 = 1854

SPEC license #: 13 Tested by: Intel Corporation Test date: Oct-2006 Hardware Avail: Nov-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	110	1278	110	1276	[Bar chart showing ratio 1276]			
175.vpr	1400	110	1269	109	1282	[Bar chart showing ratio 1282]			
176.gcc	1100	51.4	2140	51.4	2140	[Bar chart showing ratio 2140]			
181.mcf	1800	78.8	2283	78.8	2283	[Bar chart showing ratio 2283]			
186.crafty	1000	72.0	1389	72.7	1376	[Bar chart showing ratio 1376]			
197.parser	1800	124	1457	123	1462	[Bar chart showing ratio 1462]			
252.eon	1300	51.9	2504	51.8	2512	[Bar chart showing ratio 2512]			
253.perlbmk	1800	80.9	2224	81.1	2220	[Bar chart showing ratio 2220]			
254.gap	1100	52.0	2113	52.0	2113	[Bar chart showing ratio 2113]			
255.vortex	1900	57.4	3308	57.4	3308	[Bar chart showing ratio 3308]			
256.bzip2	1500	107	1401	107	1397	[Bar chart showing ratio 1397]			
300.twolf	3000	159	1883	159	1884	[Bar chart showing ratio 1884]			

Hardware

CPU: Intel(R) Pentium(TM) processor Extreme Edition 965 (3.73 GHz, 1066 MHz bus)
CPU MHz: 3733
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD per core, on chip
Secondary Cache: 2MB(I+D) per core, on chip
L3 Cache: None
Other Cache: None
Memory: 2 GB (2 1GB Micron MT16HTF12864AY-80ED4 DDR2 800, CL5)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: nVidia Quad SLI GeForce 7950 GX2 PCI Express graphics card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_CC_P_9.1.020
Microsoft Visual Studio 2005 (for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M-80.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D975XBX2 motherboard (3.73 GHz, Intel(R) Pentium(TM) processor Extreme Edition 965)

SPECint2000 = 1854

SPECint_base2000 = 1854

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2006 | Hardware Avail: Nov-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO

300.twolf: -fast -O3 +FDO shlw32m-80.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 11/2006

<http://www.intel.com/products/motherboard/D975XBX2/index.htm>

shlw32m-80.lib is the V8.0 SmartHeap library renamed to co-exist with older versions

The system bus runs at 1066 MHz