



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor E5345, 2.33 GHz

SPECfp\_rate2000 = 58.0

SPECfp\_rate\_base2000 = 58.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	99.9	74.3	4	99.9	74.3
171.swim	4	431	33.4	4	431	33.4
172.mgrid	4	271	30.8	4	271	30.8
173.applu	4	296	32.9	4	296	32.9
177.mesa	4	59.8	109	4	59.8	109
178.galgel	4	81.9	164	4	81.9	164
179.art	4	71.2	170	4	71.2	170
183.quake	4	184	32.7	4	184	32.7
187.facerec	4	112	78.5	4	112	78.5
188.amp	4	141	72.1	4	141	72.1
189.lucas	4	254	36.6	4	254	36.6
191.fma3d	4	232	42.0	4	232	42.0
200.sixtrack	4	126	40.6	4	126	40.6
301.apsi	4	215	56.1	4	215	56.1

### Hardware

CPU: Intel Xeon processor E5345 (2.33 GHz, 2x4MB L2, 1333 MHz system bus)  
CPU MHz: 2333  
FPU: Integrated  
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)  
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm, 73GB)  
Other Hardware: none

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10  
Kernel 2.6.16.21-0.8-smp on an x86\_64  
Compiler: Intel C++ and Fortran Compiler 9.1 for EM64T  
Build 20060816 (for 64-bit applications)  
File System: reiserfs  
System State: Multi-user run level 3

## Notes/Tuning Information

### GENERAL

+FDO implies feedback-directed optimization

PASS1: -prof\_gen PASS2: -prof\_use

### Optimization flags

ONESTEP=yes set for all benchmarks

### Portability flags

-DSPEC\_CPU2000\_LP64 applied to all benchmarks

178.galgel: -FI for fixed-format Fortran

### Base tuning flags

for Fortran and C programs: -fast +FDO

### Peak tuning flags

same as baseline (basepeak=true set globally)

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX200 S3, Intel Xeon processor E5345, 2.33 GHz

SPECfp\_rate2000 = 58.0

SPECfp\_rate\_base2000 = 58.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS Configuration:

Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>