



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL465c (AMD Opteron (TM) 2220)

SPECint_rate2000 = 43.2
SPECint_rate_base2000 = 38.0

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Nov-2006 Hardware Avail: Jan-2007 Software Avail: Oct-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	83.0	39.1	2	82.7	39.3
175.vpr	2	109	29.7	2	104	31.3
176.gcc	2	59.1	43.2	2	58.3	43.8
181.mcf	2	290	14.4	2	173	24.1
186.crafty	2	42.3	54.9	2	42.0	55.3
197.parser	2	142	29.4	2	111	37.5
252.eon	2	43.7	69.0	2	39.4	76.6
253.perlbnk	2	104	40.2	2	85.3	48.9
254.gap	2	63.2	40.4	2	62.3	41.0
255.vortex	2	73.3	60.2	2	66.2	66.6
256.bzip2	2	100	34.6	2	100	34.6
300.twolf	2	208	33.4	2	156	44.6

Hardware

CPU: AMD Opteron (TM) 2220
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 GB (4x2 GB PC2-5300P CL5.0)
 Disk Subsystem: 1x36 GB 10K SAS
 Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 3
 SuSE kernel 2.6.5-7.244-smp
 Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.5
 File System: Linux/ext2
 System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -Ofast +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
              -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
          -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64
Peak tuning:
 164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
 186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
 197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
 252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
          -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL465c (AMD Opteron (TM) 2220)

SPECint_rate2000 = 43.2
SPECint_rate_base2000 = 38.0

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Nov-2006 Hardware Avail: Jan-2007 Software Avail: Oct-2006

Notes/Tuning Information (Continued)

```
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```

BIOS Configuration Notes

Node Interleaving Disabled

Other Configuration Notes

Taskset utility used to bind process to CPU(s)