

# SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Dell: PowerEdge 2650  
Microsoft: IIS 5.0 and SWC 3.0

SPECweb99 = 5698

Test Date: Apr-2003  
Tester: Dell

Hardware Avail: May-2003 OS Avail: Feb-2000 HTTP Software Avail: May-2001 Sup. Software Avail: Mar-2003 SPEC license #: 55

## Hardware

Vendor: Dell  
Model: PowerEdge 2650  
Processor: 3.06 GHz Intel Xeon  
# Processors: 2 cores, 2 chips, 1 core/chip (Hyper-Threading enabled)  
Primary Cache: 12KBI+8KBD on chip  
Secondary Cache: 512KB ATC  
Other Cache: None  
Memory: 8 GB  
Disk Subsystem: 5 36GB 15KRPM drives  
Disk Controllers: Onboard Adaptec 7899  
Other Hardware: 4 Dell PowerConnect 5012

## Software

Operating System: Windows 2000 Advanced Server  
File System: NTFS  
Other Software: SP2, Intel 7.0.30 driver  
Q298896 TCP/IP and NDIS hotfix

## HTTP Software

Vendor: Microsoft  
HTTP Software: IIS 5.0 and SWC 3.0  
API: TWC 3.0  
Server Cache: None  
Log Mode: Binary CLF

## Test Sponsor

Test Date: Apr-2003  
Tested By: Dell  
SPEC License: 55

## Network

# of Controllers: 2  
Network Controllers: Intel PRO/1000 MT Dual Port Server Adapter  
# of Nets: 4  
Type of Nets: Gigabit Ethernet  
Network Speed: 1 Gb/s  
MSL (sec): 30 (Non RFC1122)  
Time-Wait (sec): 60 (Non RFC1122)  
MTU: 1500

## Clients

# of Clients: 15  
Model: Dell PowerEdge 1550  
Processor: 1.0GHz Pentium III  
# of Processors: 2  
Memory: 256MB  
Network Controller: Intel PRO/1000 XT  
Operating System: Windows XP Professional  
Compiler: Microsoft Visual C++ 6.0

## Notes/Tuning Information

### SUT Notes

1 disk OS, 1 disk access log, 3 disk software RAID0 stripe for file set  
"Sequential Memory Access" disabled in BIOS, default enabled

### Operating System Notes

Tuning parameters:

- AFD\Parameters\TransmitWorker=32, adjusts system default thread, default 16
- Control\FileSystem\NtfsDisableLastAccessUpdate=1, prevents updating LastAccess time stamp on NTFS directories
- Control\Session Manager\Memory Management\LargeSystemCache=0, limits system cache, default 1
- Control\Session Manager\Memory Management\SystemPages=0xffffffff, sets system pages
- Tcpiip\Parameters\DisableLargeSendOffload=0, enable large sends for TCP/IP
- Tcpiip\Parameters\MaxFreeTWTcbs=1098000, sets maximum number of TIME\_WAIT tcbs to 1,098,000
- Tcpiip\Parameters\MaxHashTableSize=0x10000, sets TCB hash table size to 65,536 entries, default 512
- Tcpiip\Parameters\MaxSendSegments=0x1000, max TCP segments sent consecutively to a destination, default 64
- Tcpiip\Parameters\MaxUserPort=0xffffe, sets maximum open ports to 65534
- Tcpiip\Parameters\NumTcbTablePartitions=32, sets number of independent TCB table segments, default 4
- Tcpiip\Parameters\TcpTimedWaitDelay=60, sets TIME\_WAIT parameter to 60 seconds (non-RFC 1122), default 240
- Tcpiip\Parameters\TcpWindowSize=65535, sets TCP send/receive window size, default 8192

One NIC IRQ bound per logical CPU via IntFiltr, default unbound

Intel NIC settings:

- NumTxDescriptors=4096, number of transmit descriptors, default 256
- TcpSegmentation=1, enables TCP segmentation offload, default 0

- FlowControl=0, disables flow control, default 1

# SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

## Notes/Tuning Information (Continued)

### HTTP Software Notes

- SWC\Parameters\LogDrive=L, puts log file on L: drive
- SWC\Parameters\LogFileInitialSize=0xffffffff, sets initial log file size to 4 gigabytes
- SWC\Parameters\VirtualRootName=spec99, sets virtual directory name to spec99
- SWC\Parameters\VirtualRootPath=F:\wwwroot99, sets physical path where files are located
- SWC\Parameters\SmallCachingThreshold=50, max size for small files (bytes), default system-dependent
- SWC\Parameters\LargeCachingThreshold=1200000, max size for cached files (bytes), default system-dependent
- SWC\Parameters\SmallBufferSize=0x3a, memory for caching small files (MB), default system-dependent
- SWC\Parameters\LargeBufferSize=0x1b58, memory for caching large files (MB), default system-dependent
- SWC\Parameters\SwcLockedMemorySize=0x6c, size of locked memory for SWC ops (MB), default system-dependent
- TWC CAD buffers=1152, default not set
- CGI Gateway buffers=64, default not set
- CGI Gateway bound to first CPU via Task Manager, default last CPU

### Client Notes

- Tcip\Parameters\MaxUserPort=0xfffe, sets maximum open ports to 65534
- Tcip\Parameters\TcpTimedWaitDelay=60, sets TIME\_WAIT parameter to 60 seconds (non-RFC 1122), default 240
- Tcip\Parameters\MaxFreeTWTcbs=100000, sets maximum number of TIME\_WAIT tcbs to 100,000
- Tcip\Parameters\TcpWindowSize=65535, sets TCP send/receive window size, default 8192

### Other Notes

Tuning Disclosure: See above  
Dynamic API: Dell-20001212-TWC.zip