

SPECweb99_SSL Result

```

=====
IBM : xSeries 440
Red Hat : Zeus V4.1R1
||
||
||
||
CD SPECweb99_SSL
=====

```

SPEC has discovered a bug in the SPECweb99_SSL test harness run on the client systems used in this result. The bug prevents these client systems from generating the correct SPECweb99_SSL workload. Specifically, the bug in the SPECweb99_SSL code results in the clients not generating any of the required SSL ClientKeyExchanges during the benchmark. Therefore, the results presented here are not comparable with any other SPECweb99_SSL results.

PERFORMANCE

Iteration	Conforming Simultaneous Connections
1	CD
2	CD
3	CD
Median	CD

Availability Dates

```

All Hardware      Mar-2002
HTTPS Software    Mar-2002
Operating System  May-2002
Supplemental System May-2002

```

Hardware

```

Vendor      IBM
Model       xSeries 440
Processor   1.6 GHz Intel Xeon MP
# Processors 4 cores, 4 chips, 1 core/chip
Primary Cache 12KBI + 8KBD on chip
Secondary Cache 256MB L2
Other Cache  1MB L3 cache and 32MB L4 cache
Memory      4 GB
Disk Subsystem 7 x 18GB ST318451LC
Disk Controllers On-Board Adaptec SCSI
Other Hardware 2 x Alteon ACEswitch 180

```

Software

```

Operating System  Red Hat 7.2 Linux with a 2.4.18 Kernel
File System       Ext. 2
Other Software    IBM Summit chipset patches
                  Intel 3.6.8 driver

```

HTTPS Software

```

Vendor      Red Hat
HTTPS Software Zeus V4.1R1
API         Zeus PEPP 0.6 ISAPI used for dynamic content
Server Cache None
Log Mode    Zeus Binary CLF

```

Test Sponsor

```

Test Date      Jun-2002
Tested By     IBM
SPEC License   11

```

Network

```

# of Controllers 2
Network Controllers Intel Pro 1000
# of Nets        2
Type of Nets     Gigabit Ethernet
Network Speed    1 Gb/s
MSL (sec)        30 (Non RFC1122)
Time-Wait (sec) 60 (Non RFC1122)
MTU              1500

```

Clients

```

# of Clients     10
Model            IBM xSeries 330
Processor        1.13Ghz Pentium III
# of Processors  1
Memory          256MB
Network Controller Alteon ACENIC
Operating System Windows 2000

```

Compiler Visual C++ 6.0

Benchmark Configuration

Requested Connections 1170
Fileset Size (MB) 3864.96

Notes/Tuning information

SUT Notes

- 1 disk for OS
- 5 disk software RAID0, using 64KB chunk size, for web pages
- 1 disk for logs

Operating System Notes

Tuning parameters:

- net.ipv4.ip_forward=1, default 0
 - net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
 - net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
 - net.ipv4.tcp_max_tw_buckets = 2000000, sets TCP time-wait buckets pool size, default 180000
 - net.core.rmem_max = 10000000, maximum receive socket buffer size, default 65535
 - net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
 - net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
 - net.core.wmem_default = 10000000, default send socket buffer size, default 65535
 - net.core.optmem_max = 10000000, default 10240
 - net.core.hot_list_length = 10000, maximum number of skb-heads to be cached, default 128
 - net.ipv4.tcp_rmem = 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
 - net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
 - net.ipv4.tcp_mem=30000000 30000000 30000000, maximum TCP buffer space, default 31744 32256 32768
 - fs.file-max = 81920, maximum number of open files, default 1024
- See x440config for kernel build information

HTTPS Software Notes

Zeus Configuration

- tuning!bind_any yes
- tuning!cache_files 8192
- tuning!cache_flush_interval 31536000
- tuning!cache_large_file 1048576
- tuning!cache_max_bytes 0
- tuning!cache_small_file 4096
- tuning!cache_stat_expire 31536000
- tuning!num_children 16
- tuning!so_wbuff_size 1048576
- tuning!softservers no
- tuning!unique_bind no
- tuning!use_poll yes
- tuning!cache_cooling_time 0
- tuning!cbuff_size 65536
- tuning!ssl_sessioncache_size 5011
- tuning!ssl_sessioncache_expiry 120
- tuning!ssl_keepalive yes
- tuning!ssl_diskcache yes
- tuning!keepalive yes
- tuning!sendfile yes
- tuning!sendfile_minsize 1
- tuning!sendfile_maxsize 2147483647
- tuning!listen_queue_size 8192
- tuning!so_rbuff_size 0
- tuning!modules!cgi!cleansize 0

See Zeus-tuning.txt for a description of the Zeus tuning parameters
ISAPI Source code is available in the SPECweb99 support docs as IBM-20011019_1-API.tar.gz

Test Run Details

Run Num	Conforming Connections	Percent Conform	Throughput ops/sec	Response msec	ops/sec/loadgen	Kbits/sec
=> 1	CD	CD	CD	CD	CD	CD
2	CD	CD	CD	CD	CD	CD
3	CD	CD	CD	CD	CD	CD