

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard: hp server rx5670
Zeus Technology Limited: Zeus 4.2

SPECweb99_SSL =1888

Test Date: Oct-2002
Tester: Hewlett-Packard Company

Hardware Avail: Sep-2002 OS Avail: Aug-2002 HTTPS Software Avail: Nov-2002 Sup. Software Avail: Aug-2002 SPEC license #: 3

Hardware

Vendor: Hewlett-Packard
Model: hp server rx5670
Processor: 1 GHz Intel Itanium 2
Processors: 4 cores, 4 chips, 1 core/chip
Primary Cache: 16KBI+16KBD on chip
Secondary Cache: 256KB unified on chip
Other Cache: 3072KB unified on chip
Memory: 16 GB
Disk Subsystem: 2x36GB (10K rpm)
Disk Controllers: SCSI C896 UW SE (internal)
Other Hardware: 4 x Alteon 180e Switches

Software

Operating System: HP-UX 11i v1.6
File System: See SUT Notes
Other Software: B3913DB C.05.36 HP aC++/C

HTTPS Software

Vendor: Zeus Technology Limited
HTTPS Software: Zeus 4.2
API: ISAPI
Server Cache: None
Log Mode: Binary Log Format

Test Sponsor

Test Date: Oct-2002
Tested By: Hewlett-Packard Company
SPEC License: 3

Network

of Controllers: 4
Network Controllers: HP A6847A PCI Gigabit Ethernet
of Nets: 4
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 12
Model: HP 9000/A500-5X
Processor: 550 MHz PA-8600
of Processors: 2
Memory: 4 GB
Network Controller: HP A4926A Gigabit Ethernet
Operating System: HP-UX 11i
Compiler: B3901BA B.11.11.04 HP C/ANSI C

Notes/Tuning Information

SUT Notes

1 (36 GB 10K rpm) disk with vxfs used for OS and logs
1 (36 GB 10K rpm) disk with hfs used for the file_set
Bound each Zeus instance to the processor corresponding to its NIC
Processor binding is performed by: mpsched -c cpu# -p pid
Set page size attribute for zeus.web and zeus.cgi binaries
chattr +pd 4k +pi 4k zeus.cgi
chattr +pd 64M +pi 64M zeus.web

Operating System Notes

HP-UX Tunable Parameters:
dbc_max_pct=30 Max Buffer Cache Size as Percent of RAM (50)
dbc_min_pct=30 Min bufer Cache Size as Percent of RAM (5)
maxfiles=60000 Soft File Limit per Process (60)
maxfiles_lim=60000 Hard File Limit per Process (1024)
maxssiz_64bit=0x0000000180000000 Max Stack Size for 64-Bit Procs (0x00800000)
maxuprc=10000 Max number of user processes (75)
nfile=5000 Max number of open files (790)
ninode=60000 Max number of inodes (444)
nkthread=8000 Max number of kernel threads (499)
nproc=1000 Max number of processes (276)
tcpshasz=16384 Relative Scaling Factor for TCP & IP Int. Tables(2048)
vps_ceiling=4096 Max System selected page size [KB] (16)
vps_pagesize=64 Default User page size [KB] (4)

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTPS Software Notes

Zeus Global Parameters:

```
tuning!cache_files 356750
tuning!cache_max_bytes 0
tuning!cache_small_file 0
tuning!cache_large_file 1048576
tuning!cache_stat_expire 86400
tuning!cache_flush_interval 86400
tuning!listen_queue_size 8192
tuning!multiple_accept yes
tuning!so_rbuff_size 0
tuning!so_wbuff_size 1048576
tuning!cbuff_size 65536
tuning!keepalive yes
tuning!keepalive_timeout 1200
tuning!keepalive_max -1
tuning!timeout 600
tuning!unique_bind yes
tuning!bind_any no
tuning!sendfile no
tuning!modules!cgi!cbuff_size 1048576
tuning!modules!cgi!cleansize 0
tuning!ssl_keepalive yes
tuning!ssl_sessioncache_size 256
tuning!ssl_diskcache no
tuning!softservers no
tuning!use_poll no
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!modules!isapi!enabled yes
tuning!cache_cooling_time 0
tuning!maxaccept 1024
security!enabled yes
```

HTTP API Notes

Zeus ISAPI interface used
Zeus PEPP Toolkit(0.6) used for SPECweb99_SSL dynamic content
./Configure --sendfile=no --checkconfig=yes --locking=semop

Network Notes

Networking Tunable Parameters:

```
tcp_xmit_hiwater_def=2000000 Max unsent data triggers flow control(32768)
tcp_conn_request_max=1024 Max outstanding connection reqs (20)
tcp_conn_strategy=1 Selects TCP connection strategy (0)
```

Client Notes

Client code generated with ./configure --enable-posix-threads

HP-UX Tunable Parameters:

```
max_thread_proc=800 Number of threads per process (64)
maxusers=256 Value of MAXUSERS macro (32)
ncallout=5000 Increase number of pending timeouts
nkthread=8000 Maximum number of system-wide threads (499)
ninode=5000 Maximum number of inodes (444)
nfile=4096 Maximum number of open files (790)
maxswapchunks=2048 Maximum number of swap chunks (256)
```

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Other Notes

Tuning Disclosure: HP-20020708.txt
Dynamic API: HP-20010917-API.tar.gz