

Via Vetoio 1, 67010 Coppito, L'Aquila, Italy www.di.univaq.it




Institute for Programme Structure and Data Organisation Software Design and Quality Group Am Fasanengarten 5 Karlsruhe, Germany www.sdq.ipd.kit..edu

Towards the Identification of "Guilty" Performance Antipatterns

Vittorio Cortellessa, Anne Martens, Ralf Reussner, Catia Trubiani

The problem of interpreting the results of software performance analysis is very critical. Software developers expect feedback in terms of architectural design alternatives (e.g., re-deploy a component), whereas the results of performance analysis are pure numbers. Support to the interpretation of such results that helps to fill the gap between numbers and software alternatives is still lacking. Performance antipatterns can play a key role in the search of performance problems and in the formulation of their solutions.

In this poster, we introduce a process to elaborate the analysis results and to score performance requirements, model entities and guilty performance antipatterns. We illustrate the process with exemplary values.



Keywords: Performance Prediction, Software Architecture, Antipatterns

Related Work

Xu et al.[4] present a semi-automated approach to find configuration and design improvement on the performance model level based on LQN models.

Parsons et al. [3] present a framework for detecting performance anti-patterns in Java EE architectures. The method requires an implementation of a component-based system, which can be monitored for performance properties.

Diaz Pace et al. [2] have developed the ArchE framework. ArchE assists the software architect during the design to create architectures that meet quality requirements. It helps to create architectural models and suggests improvements.

A more detailed presentation of this work can be found in [1].

References

[1] V. Cortellessa, A. Martens, R. Reussner and C. Trubiani. A Process to Effectively Identify "Guilty" Performance Antipatterns. In *Proc. of Fundamental Approaches to Software Engineering (FASE'10)*, to appear.

[2] A. Díaz Pace, H. Kim, L. Bass, P. Bianco, and F. Bachmann. Integrating quality-attribute reasoning frameworks in the ArchE design assistant. In S. Becker, F. Plasil, and R. Reussner, editors, *Proc. of 4th International Conference on the Quality of Software-Architectures (QoSA'08)*, volume 5281 of *LNCS*, pages 171--188. Springer, 2008.

[3] T. Parsons and J. Murphy. Detecting performance antipatterns in component based enterprise systems. *Journal of Object Technology*, 7(3):55--90, 2008.

[4] J. Xu. Rule-based automatic software performance diagnosis and improvement. In *Proc. of the 7th International Workshop on Software and Performance (WOSP'08)*, pages 1--12, New York, NY, USA, 2008. ACM.