



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro PDSMP-8/i Motherboard

SPECfp2000 = 1741
SPECfp_base2000 = 1734

SPEC license #01176 Tested by: Supermicro Test date: Aug-2005 Hardware Avail: Aug-2005 Software Avail: Apr-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	61.1	2619	61.2	2616	[Bar chart showing ratio 2616]			
171.swim	3100	118	2617	119	2613	[Bar chart showing ratio 2613]			
172.mgrid	1800	124	1449	124	1449	[Bar chart showing ratio 1449]			
173.applu	2100	133	1584	130	1616	[Bar chart showing ratio 1616]			
177.mesa	1400	98.7	1419	98.7	1419	[Bar chart showing ratio 1419]			
178.galgel	2900	109	2657	109	2652	[Bar chart showing ratio 2652]			
179.art	2600	76.8	3385	76.8	3385	[Bar chart showing ratio 3385]			
183.earthquake	1300	50.5	2575	48.8	2667	[Bar chart showing ratio 2667]			
187.facerec	1900	101	1888	101	1890	[Bar chart showing ratio 1890]			
188.amp	2200	238	923	238	926	[Bar chart showing ratio 926]			
189.lucas	2000	91.3	2191	91.2	2192	[Bar chart showing ratio 2192]			
191.fma3d	2100	142	1482	142	1482	[Bar chart showing ratio 1482]			
200.sixtrack	1100	173	636	173	636	[Bar chart showing ratio 636]			
301.apsi	2600	218	1193	218	1194	[Bar chart showing ratio 1194]			

Hardware

CPU: Intel Pentium D 840 Processor (3.2GHz, 800 MHz bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD/core on chip
Secondary Cache: 1024KB/core on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 X 1024MB DDR2-667 ECC Unbuffered
Disk Subsystem: 1 X IDE Maxtor DiamondMax Plus 9 250GB
Other Hardware: N/A

Software

Operating System: Windows 2003 Enterprise Server
Compiler: Intel C++ and Fortran Compiler 9.0 Build 20050430Z (32-bit)
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for 177.mesa: -fast shlw32M.lib +FDO
Base tuning for 179.art: -fast shlw32M.lib +FDO
Base tuning for 183.earthquake: -fast shlw32M.lib +FDO
Base tuning for 188.amp: -fast shlw32M.lib +FDO
Portability:
178.galgel: -FI /F32000000
191.fmma3d approved windowsdp src.alt used
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
PDSMP-8/i Motherboard

SPECfp2000 =	1741
SPECfp_base2000 =	1734

SPEC license #01176 | Tested by: Supermicro | Test date: Aug-2005 | Hardware Avail: Aug-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```
183.equake: -QxP -Oa -Qrcd -Qipo shlw32M.lib +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.ammp: -fast -Oa +FDO shlw32M.lib
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
```

Tested system was built with 1U SC816S-400 -Redundant Power Supply. Use only with Supermicro 1U chassis recommended

Product description located as of:

<http://www.supermicro.com/products/motherboard/DualCore/E7230/PDSMP-8.cfm>

The system bus runs at 800MHz