



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML570 G4 (3.0GHz, Intel Xeon processor 7041)

SPECint_rate2000 = **61.2**
SPECint_rate_base2000 = **60.9**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: May-2006 Hardware Avail: May-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	142	45.7	4	142	45.7
175.vpr	4	161	40.4	4	156	41.6
176.gcc	4	66.8	76.4	4	66.8	76.4
181.mcf	4	201	41.6	4	201	41.6
186.crafty	4	88.8	52.2	4	88.3	52.5
197.parser	4	151	55.5	4	150	55.7
252.eon	4	63.4	95.1	4	63.4	95.1
253.perlbnk	4	105	79.8	4	103	81.3
254.gap	4	87.0	58.6	4	86.4	59.0
255.vortex	4	83.2	106	4	83.1	106
256.bzip2	4	154	45.3	4	154	45.3
300.twolf	4	194	71.6	4	194	71.6

Hardware

CPU: Intel Xeon processor 7041 (3.0GHz, 2x2MB L2, 800MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16x2048MB PC2-3200 dual-rank
Disk Subsystem: 1x36GB SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib

Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -fast +FDO ONESTEP=yes

175.vpr: -fast +FDO ONESTEP=yes

176.gcc: basepeak = 1

181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -fast +FDO ONESTEP=yes

252.eon: -fast +FDO

253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -fast +FDO ONESTEP=yes

255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML570 G4 (3.0GHz, Intel Xeon processor 7041)

SPECint_rate2000 = 61.2
SPECint_rate_base2000 = 60.9

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: May-2006 Hardware Avail: May-2006 Software Avail: May-2006

Notes/Tuning Information (Continued)

256.bzip2: basepeak=1
300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Hyper-Threading Technology disabled