



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY TX150 S5, Intel Xeon processor 3060, 2.40 GHz

SPECfp\_rate2000 = 44.9

SPECfp\_rate\_base2000 = 44.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	55.4	67.0	2	55.4	67.0
171.swim	2	219	32.9	2	219	32.9
172.mgrid	2	141	29.6	2	141	29.6
173.applu	2	165	29.4	2	165	29.4
177.mesa	2	55.1	58.9	2	55.1	58.9
178.galgel	2	64.7	104	2	64.7	104
179.art	2	45.0	134	2	45.0	134
183.quake	2	79.6	37.9	2	79.6	37.9
187.facerec	2	78.6	56.0	2	78.6	56.0
188.amp	2	133	38.4	2	133	38.4
189.lucas	2	132	35.1	2	132	35.1
191.fma3d	2	133	36.6	2	133	36.6
200.sixtrack	2	121	21.1	2	121	21.1
301.apsi	2	157	38.4	2	157	38.4

### Hardware

CPU: Intel Xeon processor 3060 (2.40 GHz, 4MB L2, 1066 MHz system bus)  
CPU MHz: 2400  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1 chip  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 4096KB(I+D) on chip, per chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4x2GB DDRII-RAM PC2-4200E (CAS 4-4-4)  
Disk Subsystem: Western Digital (SATA, 7.2krpm, 160GB)  
Other Hardware: none

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10  
Kernel 2.6.16.21-0.8-smp on an x86\_64  
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T  
Build 20060120 (for 64-bit applications)  
File System: reiserfs  
System State: Multi-user run level 3

## Notes/Tuning Information

### GENERAL

+FDO implies feedback-directed optimization  
PASS1: -prof\_gen PASS2: -prof\_use

### Optimization flags

ONESTEP=yes set for all benchmarks

### Portability flags

-DSPEC\_CPU2000\_LP64 applied to all benchmarks  
178.galgel: -FI for fixed-format Fortran

### Base tuning flags

for Fortran and C programs: -fast +FDO

### Peak tuning flags

same as baseline (basepeak=true set globally)



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY TX150 S5, Intel Xeon processor 3060, 2.40 GHz

SPECfp\_rate2000 = 44.9

SPECfp\_rate\_base2000 = 44.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

## Notes/Tuning Information (Continued)

The system bus runs at 1066 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>