



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECint_rate2000 = 76.6

SPECint_rate_base2000 = 76.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	205	63.5	8	205	63.5
175.vpr	8	257	50.6	8	257	50.6
176.gcc	8	104	97.9	8	104	97.9
181.mcf	8	233	71.6	8	233	71.6
186.crafty	8	170	54.6	8	170	54.6
197.parser	8	225	74.3	8	225	74.3
252.eon	8	111	109	8	111	109
253.perlbnk	8	202	82.6	8	202	82.6
254.gap	8	136	75.3	8	136	75.3
255.vortex	8	150	118	8	150	118
256.bzip2	8	201	69.3	8	201	69.3
300.twolf	8	346	80.4	8	346	80.4

Hardware

CPU: Intel Xeon processor 7130M (3.20 GHz, 2x1MB L2, 8MB L3, 800 MHz system bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2,4 chips
Parallel: No
Primary Cache: 12k micro-ops(I) + 16KB(D) on chip, per core
Secondary Cache: 1024KB(I+D) on chip, per core
L3 Cache: 8MB on chip, per chip
Other Cache: N/A
Memory: 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)
Disk Subsystem: Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060323Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECint_rate2000 = 76.6

SPECint_rate_base2000 = 76.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>