



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3550 (1.86 GHz Xeon E5320, 8MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 77.9

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	170	87.5			
171.swim	8	691	41.7			
172.mgrid	8	424	39.4			
173.applu	8	461	42.3			
177.mesa	8	80.6	161			
178.galgel	8	109	247			
179.art	8	123	196			
183.quake	8	221	54.5			
187.facerec	8	184	96.0			
188.amp	8	219	93.2			
189.lucas	8	402	46.2			
191.fma3d	8	374	52.1			
200.sixtrack	8	156	65.4			
301.apsi	8	290	83.1			

Hardware

CPU: Intel Xeon processor E5320 (1.86 GHz, 1066 MHz bus)
 CPU MHz: 1866
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1, 2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024 MB ECC PC2-5300F
 Disk Subsystem: 73GB SAS 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```