



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint®_rate2006 = 167

HP Integrity rx7640
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECint_rate_base2006 = 159

CPU2006 license: 03


Test date: Dec-2006

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006



Hardware

CPU Name: Dual-Core Intel Itanium 2 9040
 CPU Characteristics: 1.6GHz/18MB, 533MHz FSB
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 16 cores, 8 chips, 2 cores/chip
 CPU(s) orderable: 1-8 chips
 Primary Cache: 16 KB I + 16 KB D on chip per core
 Secondary Cache: 1 MB I + 256 KB D on chip per core
 L3 Cache: 9 MB I+D on chip per core
 Other Cache: None
 Memory: 64 GB (32x2GB DIMMs)
 Disk Subsystem: 73GB 15K RPM SCSI
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux AS release 4 (Update 4)
 Compiler: Intel C++ Compiler 9.1 for Linux (Build 20061105)
 Auto Parallel: No
 File System: ext3
 System State: Multi-user
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 Other Software: MicroQuill Smartheap 8.0



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 167

HP Integrity rx7640
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECint_rate_base2006 = 159

CPU2006 license: 03

Test date: Dec-2006

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	1139	137	<u>1112</u>	<u>141</u>	1111	141	16	939	166	941	166	<u>941</u>	<u>166</u>
401.bzip2	16	<u>1121</u>	<u>138</u>	1122	138	1120	138	16	<u>1109</u>	<u>139</u>	1108	139	1110	139
403.gcc	16	1309	98.4	<u>1301</u>	<u>99.0</u>	1293	99.6	16	1198	107	1196	108	<u>1197</u>	<u>108</u>
429.mcf	16	<u>1427</u>	<u>102</u>	1405	104	1435	102	16	<u>1427</u>	<u>102</u>	1405	104	1435	102
445.gobmk	16	<u>1035</u>	<u>162</u>	1037	162	1035	162	16	<u>916</u>	<u>183</u>	921	182	916	183
456.hammer	16	368	406	367	406	<u>367</u>	<u>406</u>	16	368	406	367	406	<u>367</u>	<u>406</u>
458.sjeng	16	<u>1461</u>	<u>132</u>	1461	132	1461	133	16	1281	151	1281	151	<u>1281</u>	<u>151</u>
462.libquantum	16	985	337	877	378	<u>883</u>	<u>376</u>	16	985	337	877	378	<u>883</u>	<u>376</u>
464.h264ref	16	<u>1162</u>	<u>305</u>	1161	305	1162	305	16	<u>1162</u>	<u>305</u>	1161	305	1162	305
471.omnetpp	16	1451	68.9	<u>1450</u>	<u>69.0</u>	1450	69.0	16	<u>1407</u>	<u>71.1</u>	1406	71.1	1407	71.1
473.astar	16	749	150	744	151	<u>748</u>	<u>150</u>	16	<u>724</u>	<u>155</u>	726	155	721	156
483.xalancbmk	16	<u>881</u>	<u>125</u>	881	125	884	125	16	864	128	<u>862</u>	<u>128</u>	862	128

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

stacksize set to unlimited prior to run

Platform Notes

System was configured as a single partition with 2 cells and 4 processors (8 cores) per cell. Memory was configured as 100% cell local.

The following config file entry was used to bind processes to cores using the Linux "numactl" utility:
submit = let "MYNUM=\$SPECCOPYNUM" ; let "NODE=\$MYNUM/8" ; numactl --cpubind \ \$NODE --membind \ \$NODE \$command

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 167

HP Integrity rx7640
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECint_rate_base2006 = 159

CPU2006 license: 03

Test date: Dec-2006

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Base Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_IA64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

```

Base Optimization Flags

C benchmarks:

-fast -IPF_fp_relaxed -ansi-alias

C++ benchmarks:

```

-fast -IPF_fp_relaxed -ansi-alias -Wl,-z,muldefs
/opt/SmartHeap_8/lib/libsmartheapC64.a
/opt/SmartHeap_8/lib/libsmartheap64.a

```

Peak Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```

400.perlbench: -prof_gen(pass 1) -prof_use(pass 2) -fast -IPF_fp_relaxed
-ansi-alias

```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 167

HP Integrity rx7640
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECint_rate_base2006 = 159

CPU2006 license: 03

Test date: Dec-2006

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Peak Optimization Flags (Continued)

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hmmmer: basepeak = yes

458.sjeng: Same as 400.perlbench

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -prof_gen(pass 1) -prof_use(pass 2) -fast -IPF_fp_relaxed
-ansi-alias -Wl,-z,muldefs
/opt/SmartHeap_8/lib/libsmartheapC64.a
/opt/SmartHeap_8/lib/libsmartheap64.a

473.astar: -prof_gen(pass 1) -prof_use(pass 2) -fast -IPF_fp_relaxed
-ansi-alias -inline-factor=150 -Wl,-z,muldefs
/opt/SmartHeap_8/lib/libsmartheapC64.a
/opt/SmartHeap_8/lib/libsmartheap64.a

483.xalancbmk: Same as 471.omnetpp

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/IPF_intel91_flags.20090715.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/IPF_intel91_flags.20090715.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:55:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 9 January 2007.