



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp[®]2006 = 14.1

NovaScale T840 (3.00 GHz, Intel Xeon 5160)

SPECfp_base2006 = 14.1

CPU2006 license: 3


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2007

Hardware Availability: Jul-2006

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon 5160
 CPU Characteristics: 3.0GHz, 1332MHz bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip

Software

Operating System: Windows Server 2003 Enterprise X64 Edition
 Compiler: Intel C++ Compiler for 32-bit Version 9.1.033
 Build 20061103Z Package ID: W_CC_C_9.1.033
 Intel Fortran Compiler for 32-bit Version 9.1.033
 Build 20061103Z Package ID: W_FC_C_9.1.033
 Visual Studio .NET 2003 (for libraries)

Auto Parallel: No
 File System: NTFS
 System State: Default

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 14.1

NovaScale T840 (3.00 GHz, Intel Xeon 5160)

SPECfp_base2006 = 14.1

CPU2006 license: 3

Test date: Feb-2007

Test sponsor: Bull SAS

Hardware Availability: Jul-2006

Tested by: Bull SAS

Software Availability: Dec-2006

L3 Cache: None
Other Cache: None
Memory: 8 GB (667 MHz ECC CL5 DDR2 FB-DIMM)
Disk Subsystem: 3x73GB SCSI 15000 rpm
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: Not Applicable
Other Software: MicroQuill SmartHeap Library 8.0 (shIW32M.lib)

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	783	17.4	780	17.4	<u>781</u>	<u>17.4</u>	783	17.4	780	17.4	<u>781</u>	<u>17.4</u>
416.gamess	1112	17.6	<u>1112</u>	<u>17.6</u>	1111	17.6	1112	17.6	<u>1112</u>	<u>17.6</u>	1111	17.6
433.milc	985	9.32	983	9.34	<u>983</u>	<u>9.34</u>	985	9.32	983	9.34	<u>983</u>	<u>9.34</u>
434.zeusmp	639	14.2	638	14.3	<u>638</u>	<u>14.3</u>	639	14.2	638	14.3	<u>638</u>	<u>14.3</u>
435.gromacs	<u>414</u>	<u>17.3</u>	414	17.3	414	17.3	<u>414</u>	<u>17.3</u>	414	17.3	414	17.3
436.cactusADM	793	15.1	<u>792</u>	<u>15.1</u>	792	15.1	793	15.1	<u>792</u>	<u>15.1</u>	792	15.1
437.leslie3d	793	11.9	790	11.9	<u>792</u>	<u>11.9</u>	793	11.9	790	11.9	<u>792</u>	<u>11.9</u>
444.namd	530	15.1	530	15.1	<u>530</u>	<u>15.1</u>	530	15.1	530	15.1	<u>530</u>	<u>15.1</u>
447.dealII	583	19.6	<u>583</u>	<u>19.6</u>	583	19.6	583	19.6	<u>583</u>	<u>19.6</u>	583	19.6
450.soplex	706	11.8	705	11.8	<u>705</u>	<u>11.8</u>	706	11.8	705	11.8	<u>705</u>	<u>11.8</u>
453.povray	250	21.3	250	21.3	<u>250</u>	<u>21.3</u>	250	21.3	250	21.3	<u>250</u>	<u>21.3</u>
454.calculix	605	13.6	604	13.7	<u>604</u>	<u>13.7</u>	605	13.6	604	13.7	<u>604</u>	<u>13.7</u>
459.GemsFDTD	<u>975</u>	<u>10.9</u>	975	10.9	975	10.9	<u>975</u>	<u>10.9</u>	975	10.9	975	10.9
465.tonto	800	12.3	<u>800</u>	<u>12.3</u>	801	12.3	800	12.3	<u>800</u>	<u>12.3</u>	801	12.3
470.lbm	2262	6.07	<u>2262</u>	<u>6.07</u>	2262	6.07	2262	6.07	<u>2262</u>	<u>6.07</u>	2262	6.07
481.wrf	699	16.0	700	16.0	<u>699</u>	<u>16.0</u>	699	16.0	700	16.0	<u>699</u>	<u>16.0</u>
482.sphinx3	1005	19.4	<u>1005</u>	<u>19.4</u>	1005	19.4	1005	19.4	<u>1005</u>	<u>19.4</u>	1005	19.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 14.1

NovaScale T840 (3.00 GHz, Intel Xeon 5160)

SPECfp_base2006 = 14.1

CPU2006 license: 3

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2007

Hardware Availability: Jul-2006

Software Availability: Dec-2006

Base Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc7.1 -Qc99 ifort

Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore

444.namd: -TP

447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG

-DBOOST_NO_INTRINSIC_WCHAR_T

453.povray: -DSPEC_CPU_WINDOWS_ICL

454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase

481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:

-fast /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:

-fast -Qcxx_features /F950000000 shlw32m.lib

-link /FORCE:MULTIPLE

Fortran benchmarks:

-fast /F950000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

-fast /F950000000 -link /FORCE:MULTIPLE

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 3



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 14.1

NovaScale T840 (3.00 GHz, Intel Xeon 5160)

SPECfp_base2006 = 14.1

CPU2006 license: 3

Test date: Feb-2007

Test sponsor: Bull SAS

Hardware Availability: Jul-2006

Tested by: Bull SAS

Software Availability: Dec-2006

Peak Optimization Flags (Continued)

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: basepeak = yes

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: basepeak = yes

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags.20090714.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags.20090714.00.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 14.1

NovaScale T840 (3.00 GHz, Intel Xeon 5160)

SPECfp_base2006 = 14.1

CPU2006 license: 3

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2007

Hardware Availability: Jul-2006

Software Availability: Dec-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:41:40 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 March 2007.