



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp®_rate2006 = 70.9

Fujitsu SPARC Enterprise M4000

SPECfp_rate_base2006 = 67.2

CPU2006 license: 19


Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Apr-2007

Hardware Availability: May-2007

Software Availability: Jul-2007



Hardware

CPU Name: SPARC64 VI
 CPU Characteristics:
 CPU MHz: 2150
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip, 2 threads/core
 CPU(s) orderable: 1 or 2 CPUM; each CPUM contains 2 CPU chips
 Primary Cache: 128 KB I + 128 KB D on chip per core
 Secondary Cache: 5 MB I+D on chip per chip

Continued on next page

Software

Operating System: Solaris 10 7/07 (build s10s_u4wos_04)
 Compiler: Sun Studio 12 (build 44.0)
 Auto Parallel: No
 File System: ufs
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: None



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp_rate2006 = 70.9

Fujitsu SPARC Enterprise M4000

SPECfp_rate_base2006 = 67.2

CPU2006 license: 19

Test date: Apr-2007

Test sponsor: Fujitsu Limited

Hardware Availability: May-2007

Tested by: Sun Microsystems

Software Availability: Jul-2007

L3 Cache: None
Other Cache: None
Memory: 64 GB (32 x 2 GB)
Disk Subsystem: 73 GB SEAGATE ST973401L 10K RPM Ultra320 SCSI
Other Hardware: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	<u>3030</u>	<u>71.8</u>	3035	71.6	3026	71.9	16	<u>3030</u>	<u>71.8</u>	3035	71.6	3026	71.9
416.gamess	16	<u>4280</u>	<u>73.2</u>	4280	73.2	4277	73.3	8	<u>2020</u>	<u>77.5</u>	2018	77.6	2020	77.5
433.milc	16	3616	40.6	3594	40.9	<u>3604</u>	<u>40.8</u>	16	<u>3571</u>	<u>41.1</u>	3554	41.3	3575	41.1
434.zeusmp	16	<u>2632</u>	<u>55.3</u>	2633	55.3	2631	55.3	16	<u>2625</u>	<u>55.5</u>	2625	55.5	2626	55.4
435.gromacs	16	1533	74.5	<u>1532</u>	<u>74.6</u>	1529	74.7	8	700	81.6	701	81.4	<u>701</u>	<u>81.4</u>
436.cactusADM	16	<u>1743</u>	<u>110</u>	1743	110	1738	110	16	<u>1743</u>	<u>110</u>	1743	110	1738	110
437.leslie3d	16	<u>2389</u>	<u>62.9</u>	2391	62.9	2386	63.0	16	<u>2389</u>	<u>62.9</u>	2391	62.9	2386	63.0
444.namd	16	1728	74.3	1728	74.3	<u>1728</u>	<u>74.3</u>	8	799	80.3	<u>800</u>	<u>80.2</u>	803	79.9
447.dealII	16	<u>1758</u>	<u>104</u>	1794	102	1741	105	16	<u>1689</u>	<u>108</u>	1710	107	1675	109
450.soplex	16	2886	46.2	2896	46.1	<u>2889</u>	<u>46.2</u>	16	<u>2806</u>	<u>47.6</u>	2807	47.5	2797	47.7
453.povray	16	<u>1327</u>	<u>64.1</u>	1324	64.3	1331	63.9	8	416	102	417	102	<u>416</u>	<u>102</u>
454.calculix	16	1428	92.4	1426	92.5	<u>1428</u>	<u>92.5</u>	16	1428	92.4	1426	92.5	<u>1428</u>	<u>92.5</u>
459.GemsFDTD	16	3839	44.2	<u>3839</u>	<u>44.2</u>	3841	44.2	16	<u>3839</u>	<u>44.2</u>	3864	43.9	3826	44.4
465.tonto	16	<u>1974</u>	<u>79.8</u>	1995	78.9	1960	80.3	8	866	90.9	861	91.4	<u>863</u>	<u>91.2</u>
470.lbm	16	4431	49.6	4418	49.8	<u>4418</u>	<u>49.8</u>	16	4431	49.6	4418	49.8	<u>4418</u>	<u>49.8</u>
481.wrf	16	2102	85.0	<u>2110</u>	<u>84.7</u>	2114	84.5	16	2102	85.0	<u>2110</u>	<u>84.7</u>	2114	84.5
482.sphinx3	16	<u>5101</u>	<u>61.1</u>	5098	61.2	5105	61.1	16	<u>5101</u>	<u>61.1</u>	5098	61.2	5105	61.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Processes were bound to cores using "submit" and "pbind".

These shell commands request use of 4MB pages:

```
export LD_PRELOAD=mpss.so.1
export MPSSHEAP=4MB
export MPSSSTACK=4MB
```

ulimit -s 131072 was used to limit the space consumed by the stack (and therefore make more space available to the heap).

The "webconsole" service was turned off using
svcadm disable webconsole



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp_rate2006 = 70.9

Fujitsu SPARC Enterprise M4000

SPECfp_rate_base2006 = 67.2

CPU2006 license: 19

Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Apr-2007

Hardware Availability: May-2007

Software Availability: Jul-2007

Platform Notes

"CPUM" = CPU Module; each module holds two CPU chips.

Memory is 8-way interleaved by filling all slots with the same capacity DIMMs.

This result was measured using a Sun SPARC Enterprise M4000 Server. Note that the Fujitsu SPARC Enterprise M4000 and Sun SPARC Enterprise M4000 are electrically equivalent.

Base Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

Base Optimization Flags

C benchmarks:

-fast -fma=fused -xcache=128/64/2:5120/256/10 -xipo=2 -xpagesize=4M
-xprefetch_level=2 -xprefetch=latx:2 -xalias_level=std
-xprefetch_level=3 -xprefetch_auto_type=indirect_array_access

C++ benchmarks:

-xdepend -library=stlport4 -fast -fma=fused
-xcache=128/64/2:5120/256/10 -xipo=2 -xpagesize=4M -xprefetch_level=2
-xprefetch=latx:2 -xalias_level=compatible

Fortran benchmarks:

-fast -fma=fused -xcache=128/64/2:5120/256/10 -xipo=2 -xpagesize=4M
-xprefetch_level=2 -xprefetch=latx:2

Benchmarks using both Fortran and C:

-fast(cc) -fast(f90) -fma=fused -xcache=128/64/2:5120/256/10 -xipo=2
-xpagesize=4M -xprefetch_level=2 -xprefetch=latx:2 -xalias_level=std
-xprefetch_level=3 -xprefetch_auto_type=indirect_array_access



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp_rate2006 = 70.9

Fujitsu SPARC Enterprise M4000

SPECfp_rate_base2006 = 67.2

CPU2006 license: 19

Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Apr-2007

Hardware Availability: May-2007

Software Availability: Jul-2007

Base Other Flags

C benchmarks:

-xjobs=8 -V -#

C++ benchmarks:

-xjobs=8 -verbose=diags,version

Fortran benchmarks:

-xjobs=8 -V -v

Benchmarks using both Fortran and C:

-xjobs=8 -V -# -v

Peak Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

Peak Optimization Flags

C benchmarks:

433.milc: -fast -xcache=128/64/2:5120/256/10 -xpagesize=4M -xipo=2
-xprefetch_level=2 -fsimple=1
-xprefetch_auto_type=indirect_array_access
-W2,-Ainline:rs=400 -xalias_level=std -fma=fused
-xprefetch=latx:3

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xdepend -library=stlport4 -fast
-xcache=128/64/2:5120/256/10 -xpagesize=4M
-xalias_level=compatible -xprefetch_level=1 -fma=fused
-xprefetch=latx:3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp_rate2006 = 70.9

Fujitsu SPARC Enterprise M4000

SPECfp_rate_base2006 = 67.2

CPU2006 license: 19

Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Apr-2007

Hardware Availability: May-2007

Software Availability: Jul-2007

Peak Optimization Flags (Continued)

447.dealIII: -xdepend -library=stlport4
 -xprofile=collect:./feedback(pass 1)
 -xprofile=use:./feedback(pass 2) -fast
 -xcache=128/64/2:5120/256/10 -xpagesize=4M
 -xalias_level=compatible -xipo=2 -xrestrict -fma=fused
 -xprefetch=latx:4.5

450.soplex: -xdepend -library=stlport4
 -xprofile=collect:./feedback(pass 1)
 -xprofile=use:./feedback(pass 2) -fast
 -xcache=128/64/2:5120/256/10 -xpagesize=4M
 -xalias_level=compatible -xipo=2 -xprefetch_level=2
 -fsimple=0 -xrestrict
 -xprefetch_auto_type=indirect_array_access
 -Qoption cg -Qlp-ol=1 -Qoption cg -Qlp-it=3
 -Qoption cg -Qlp-imb=1 -Qoption iropt -Apf:pdl=3

453.povray: -xdepend -library=stlport4
 -xprofile=collect:./feedback(pass 1)
 -xprofile=use:./feedback(pass 2) -fast
 -xcache=128/64/2:5120/256/10 -xpagesize=4M
 -xalias_level=compatible -xipo=2 -xrestrict -fma=fused

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -fast -xcache=128/64/2:5120/256/10 -xpagesize=4M -xipo=2
-xprefetch_level=2 -fma=fused

434.zeusmp: -fast -xcache=128/64/2:5120/256/10 -xpagesize=4M -xipo=2
-fma=fused -lmopt

437.leslie3d: basepeak = yes

459.GemsFDTD: -fast -xcache=128/64/2:5120/256/10 -xpagesize=4M -fsimple=1
-xprefetch_level=2 -fma=fused -xprefetch=latx:2

465.tonto: -fast -xcache=128/64/2:5120/256/10 -xpagesize=4M -xipo=2
-xprefetch=latx:12 -lfast

Benchmarks using both Fortran and C:

435.gromacs: -xprofile=collect:./feedback(pass 1)
 -xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
 -xcache=128/64/2:5120/256/10 -xpagesize=4M -xipo=2
 -xinline= -xarch=generic -xchip=generic -fsimple=0
 -fma=fused

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

SPECfp_rate2006 = 70.9

Fujitsu SPARC Enterprise M4000

SPECfp_rate_base2006 = 67.2

CPU2006 license: 19

Test sponsor: Fujitsu Limited

Tested by: Sun Microsystems

Test date: Apr-2007

Hardware Availability: May-2007

Software Availability: Jul-2007

Peak Optimization Flags (Continued)

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

Peak Other Flags

C benchmarks:

-xjobs=8 -V -#

C++ benchmarks:

-xjobs=8 -verbose=diags,version

Fortran benchmarks:

-xjobs=8 -V -v

Benchmarks using both Fortran and C:

-xjobs=8 -V -# -v

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12.20090714.02.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12.20090714.02.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.

Report generated on Tue Jul 22 11:12:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 3 May 2007.