



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

### SPECfp®\_rate2006 = 22.6

ProLiant DL380 G5  
(2.0 GHz, Intel Xeon processor 5130)

### SPECfp\_rate\_base2006 = 20.8

CPU2006 license: 3


Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Sep-2007

Hardware Availability: Jun-2006

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon 5130  
 CPU Characteristics: 2.0 GHz, 4 MB L2 shared, 1333 MHz system bus  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 or 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) SP1  
 kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ and Fortran Compiler for Linux32 and  
 Linux64 version 10.1  
 Build 20070725  
 Auto Parallel: No  
 File System: ext2  
 System State: Multi-user run level 3  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp\_rate2006 = 22.6

ProLiant DL380 G5  
(2.0 GHz, Intel Xeon processor 5130)

SPECfp\_rate\_base2006 = 20.8

CPU2006 license: 3  
Test sponsor: Hewlett-Packard Company  
Tested by: Hewlett-Packard Company

Test date: Sep-2007  
Hardware Availability: Jun-2006  
Software Availability: Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 8 GB (8x1 GB PC2-5300F CL5)  
Disk Subsystem: 1x72 GB 10 K SAS  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: binutils-2.17.50

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	1192	22.8	<u>1192</u>	<u>22.8</u>	1192	22.8	2	<u>1121</u>	<u>24.2</u>	1121	24.2	1122	24.2
416.gamess	2	1392	28.1	1387	28.2	<u>1390</u>	<u>28.2</u>	2	<u>1378</u>	<u>28.4</u>	1370	28.6	1381	28.4
433.milc	2	1280	14.3	<u>1280</u>	<u>14.3</u>	1279	14.4	2	1283	14.3	<u>1283</u>	<u>14.3</u>	1282	14.3
434.zeusmp	2	<u>864</u>	<u>21.1</u>	863	21.1	864	21.1	2	862	21.1	863	21.1	<u>862</u>	<u>21.1</u>
435.gromacs	2	579	24.6	<u>579</u>	<u>24.7</u>	579	24.7	2	574	24.9	<u>574</u>	<u>24.9</u>	574	24.9
436.cactusADM	2	1008	23.7	<u>1001</u>	<u>23.9</u>	998	23.9	2	924	25.9	<u>913</u>	<u>26.2</u>	905	26.4
437.leslie3d	2	1264	14.9	<u>1268</u>	<u>14.8</u>	1270	14.8	2	1268	14.8	1275	14.7	<u>1271</u>	<u>14.8</u>
444.namd	2	758	21.2	756	21.2	<u>757</u>	<u>21.2</u>	2	<u>754</u>	<u>21.3</u>	754	21.3	755	21.2
447.dealII	2	662	34.6	<u>663</u>	<u>34.5</u>	663	34.5	2	<u>613</u>	<u>37.3</u>	613	37.3	611	37.4
450.soplex	2	1029	16.2	<u>1026</u>	<u>16.3</u>	1025	16.3	2	947	17.6	948	17.6	<u>947</u>	<u>17.6</u>
453.povray	2	334	31.8	<u>334</u>	<u>31.9</u>	334	31.9	2	<u>282</u>	<u>37.8</u>	282	37.8	282	37.8
454.calculix	2	<u>786</u>	<u>21.0</u>	786	21.0	786	21.0	2	549	30.1	<u>549</u>	<u>30.0</u>	552	29.9
459.GemsFDTD	2	1645	12.9	1611	13.2	<u>1618</u>	<u>13.1</u>	2	1558	13.6	1568	13.5	<u>1561</u>	<u>13.6</u>
465.tonto	2	804	24.5	<u>808</u>	<u>24.4</u>	814	24.2	2	780	25.2	786	25.0	<u>784</u>	<u>25.1</u>
470.lbm	2	2627	10.5	<u>2629</u>	<u>10.5</u>	2630	10.4	2	<u>1748</u>	<u>15.7</u>	1748	15.7	1749	15.7
481.wrf	2	<u>909</u>	<u>24.6</u>	909	24.6	909	24.6	2	908	24.6	910	24.6	<u>908</u>	<u>24.6</u>
482.sphinx3	2	1678	23.2	<u>1677</u>	<u>23.2</u>	1672	23.3	2	<u>1578</u>	<u>24.7</u>	1578	24.7	1580	24.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'/usr/bin/taskset' used to bind processes to CPUs  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to 200M

## Platform Notes

BIOS configuration:  
Power Regulator set to Static High Performance Mode



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 22.6**

ProLiant DL380 G5  
(2.0 GHz, Intel Xeon processor 5130)

**SPECfp\_rate\_base2006 = 20.8**

**CPU2006 license:** 3

**Test date:** Sep-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jun-2006

**Tested by:** Hewlett-Packard Company

**Software Availability:** Nov-2007

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

**SPECfp\_rate2006 = 22.6**

ProLiant DL380 G5  
(2.0 GHz, Intel Xeon processor 5130)

**SPECfp\_rate\_base2006 = 20.8**

**CPU2006 license:** 3

**Test date:** Sep-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jun-2006

**Tested by:** Hewlett-Packard Company

**Software Availability:** Nov-2007

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp\_rate2006 = 22.6

ProLiant DL380 G5  
(2.0 GHz, Intel Xeon processor 5130)

SPECfp\_rate\_base2006 = 20.8

CPU2006 license: 3

Test date: Sep-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jun-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL380 G5  
(2.0 GHz, Intel Xeon processor 5130)

**SPECfp\_rate2006 = 22.6**

**SPECfp\_rate\_base2006 = 20.8**

**CPU2006 license:** 3  
**Test sponsor:** Hewlett-Packard Company  
**Tested by:** Hewlett-Packard Company

**Test date:** Sep-2007  
**Hardware Availability:** Jun-2006  
**Software Availability:** Nov-2007

The flags file that was used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-flags.20090714.html>

You can also download the XML flags source by saving the following link:  
<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-flags.20090714.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 14:46:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 16 October 2007.