



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML350 G5
(3.16 GHz, Intel Xeon processor X5460)

SPECfp[®]_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Jan-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Hardware

CPU Name: Intel Xeon X5460
CPU Characteristics: 3.16 GHz, 2x6 MB L2 shared, 1333 MHz system bus
CPU MHz: 3166
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip / 6 MB shared / 2 cores
L3 Cache: None
Other Cache: None
Memory: 32 GB (8x4 GB PC2-5300F CL5)
Disk Subsystem: 1x72 GB 15 K SAS
Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1
Kernel 2.6.16.46-0.12-smp
Compiler: Intel C++ Compiler for applications running on IA-32 and Intel 64, Version 10.1
Build 20070913 Package ID: l_cc_p_10.1.008
Intel Fortran Compiler for applications running on IA-32 and Intel 64, Version 10.1
Build 20070913 Package ID: l_cc_p_10.1.008
Auto Parallel: Yes
File System: ext2
System State: Multi-user run level 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: binutils-2.17.50

Non-Compliant



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML350 G5
(3.16 GHz, Intel Xeon processor X5460)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Jan-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	8	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC	NC	NC		
416.gamess	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
433.milc	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
434.zeusmp	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
435.gromacs	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
436.cactusADM	8	NC	NC	NC	NC	NC	NC	1	NC	NC	NC	NC	NC	NC		
437.leslie3d	8	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC	NC	NC		
444.namd	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
447.dealII	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
450.soplex	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
453.povray	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
454.calculix	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
459.GemsFDTD	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
465.tonto	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
470.lbm	8	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC	NC	NC		
481.wrf	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC		
482.spm	8	NC	NC	NC	NC	NC	NC	4	NC	NC	NC	NC	NC	NC		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML350 G5
(3.16 GHz, Intel Xeon processor X5460)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Jan-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Platform Notes

BIOS configuration:

Power Regulator set to Static High Performance Mode
Adjacent Sector Prefetch Disabled
Hardware Prefetcher Disabled

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gom3drt: -DSPEC_CPU_LP64
433.mmc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.le3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML350 G5
(3.16 GHz, Intel Xeon processor X5460)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Jan-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Base Portability Flags (Continued)

465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

(as noted below):
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

482.milc: icc

C++ benchmarks (except as noted below):
icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML350 G5
(3.16 GHz, Intel Xeon processor X5460)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Jan-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Peak Compiler Invocation (Continued)

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
448.povray: -DSPEC_CPU_LP64
454.culix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML350 G5
(3.16 GHz, Intel Xeon processor X5460)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Jan-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

411.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML350 G5
(3.16 GHz, Intel Xeon processor X5460)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Jan-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-recursive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-fp-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-fp-flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 16:03:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 January 2008.