



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®_rate2006 = Not Run

IBM System x3550 (Intel Xeon E5440)

SPECint_rate_base2006 = 107

CPU2006 license: 11


Test date: Dec-2007

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5440
 CPU Characteristics: 1333MHz system bus
 CPU MHz: 2833
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 x 2 GB DDR2-5300F ECC)
 Disk Subsystem: 1 x 36 GB SAS, 15000 RPM
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64), Kernel 2.6.16.21-0.8-smp
 Compiler: Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: No
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 32-bit
 Peak Pointers: Not Applicable
 Other Software: MicroQuill SmartHeap 8.1 Binutils 2.17.50.0.15



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = Not Run

IBM System x3550 (Intel Xeon E5440)

SPECint_rate_base2006 = 107

CPU2006 license: 11

Test date: Dec-2007

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|----------------|--------|------------|-------------|------------|-------------|-------------|-------------|--------|---------|-------|---------|-------|---------|-------|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 8 | 567 | 138 | 561 | 139 | 563 | 139 | | | | | | | |
| 401.bzip2 | 8 | 782 | 98.8 | 798 | 96.7 | 784 | 98.5 | | | | | | | |
| 403.gcc | 8 | 669 | 96.3 | 672 | 95.9 | 672 | 95.9 | | | | | | | |
| 429.mcf | 8 | 903 | 80.8 | 906 | 80.5 | 908 | 80.4 | | | | | | | |
| 445.gobmk | 8 | 597 | 141 | 599 | 140 | 599 | 140 | | | | | | | |
| 456.hmmer | 8 | 641 | 116 | 642 | 116 | 641 | 116 | | | | | | | |
| 458.sjeng | 8 | 722 | 134 | 722 | 134 | 723 | 134 | | | | | | | |
| 462.libquantum | 8 | 3061 | 54.1 | 3063 | 54.1 | 3062 | 54.1 | | | | | | | |
| 464.h264ref | 8 | 748 | 237 | 748 | 237 | 748 | 237 | | | | | | | |
| 471.omnetpp | 8 | 691 | 72.4 | 691 | 72.3 | 690 | 72.5 | | | | | | | |
| 473.astar | 8 | 704 | 79.7 | 703 | 79.8 | 702 | 80.0 | | | | | | | |
| 483.xalancbmk | 8 | 439 | 126 | 438 | 126 | 438 | 126 | | | | | | | |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All benchmarks compiled in 32-bit mode

Hardware Sector Prefetch Disabled and Adjacent Sector Prefetch Disabled

Powersaved dameon was disabled in OS

taskset utility used to bind CPU(s) to processes

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = Not Run

IBM System x3550 (Intel Xeon E5440)

SPECint_rate_base2006 = 107

CPU2006 license: 11

Test date: Dec-2007

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Base Optimization Flags

C benchmarks:

```
-fast -inline-calloc -opt-malloc-options=3
```

C++ benchmarks:

```
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.13.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.13.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 16:29:46 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 February 2008.