



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems	SPECfp®2006 =	23.6
Sun SPARC Enterprise M8000	SPECfp_base2006 =	20.9

CPU2006 license: 6


Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2008

Hardware Availability: Apr-2007

Software Availability: May-2008



Hardware

CPU Name: SPARC64 VI
CPU Characteristics:
CPU MHz: 2280
FPU: Integrated
CPU(s) enabled: 32 cores, 16 chips, 2 cores/chip, 2 threads/core
CPU(s) orderable: 1 to 4 CMUs; each CMU contains 2 or 4 chips
Primary Cache: 128 KB I + 128 KB D on chip per core
Secondary Cache: 5 MB I+D on chip per chip

Software

Operating System: Solaris 10 5/08 s10s_u5wos_08
Compiler: Sun Studio 12, see patch information below
Auto Parallel: Yes
File System: ufs
System State: Default
Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: None

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems

Sun SPARC Enterprise M8000

SPECfp2006 = 23.6

SPECfp_base2006 = 20.9

CPU2006 license: 6

Test date: Mar-2008

Test sponsor: Sun Microsystems

Hardware Availability: Apr-2007

Tested by: Sun Microsystems

Software Availability: May-2008

L3 Cache: None
 Other Cache: None
 Memory: 256 GB (128 x 2 GB DIMMs)
 Disk Subsystem: 73 GB 10,000 RPM Fujitsu MAY2073RC SAS
 Other Hardware: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio								
410.bwaves	38.9	350	38.1	356	37.8	359	33.1	411	33.0	411	33.0	412
416.gamess	1974	9.92	1973	9.92	1973	9.92	1932	10.1	1932	10.1	1931	10.1
433.milc	1165	7.88	1166	7.88	1069	8.58	828	11.1	828	11.1	838	11.0
434.zeusmp	1071	8.50	1071	8.50	1070	8.50	1071	8.50	1071	8.50	1070	8.50
435.gromacs	719	9.93	719	9.93	720	9.92	650	11.0	651	11.0	652	11.0
436.cactusADM	52.6	227	53.6	223	53.2	224	52.7	227	53.0	225	52.2	229
437.leslie3d	252	37.3	254	37.0	252	37.3	205	45.8	206	45.7	205	45.9
444.namd	768	10.4	767	10.4	767	10.4	748	10.7	748	10.7	748	10.7
447.dealII	885	12.9	889	12.9	887	12.9	864	13.2	831	13.8	870	13.2
450.soplex	1137	7.34	1139	7.32	1139	7.32	968	8.61	963	8.66	955	8.74
453.povray	551	9.65	549	9.70	550	9.67	392	13.6	389	13.7	391	13.6
454.calculix	689	12.0	688	12.0	687	12.0	669	12.3	666	12.4	665	12.4
459.GemsFDTD	249	42.6	249	42.7	248	42.7	249	42.6	249	42.7	248	42.7
465.tonto	1185	8.30	1183	8.32	1184	8.31	736	13.4	736	13.4	736	13.4
470.lbm	57.6	239	57.7	238	57.7	238	55.4	248	55.4	248	55.5	247
481.wrf	731	15.3	731	15.3	734	15.2	731	15.3	731	15.3	734	15.2
482.sphinx3	1966	9.91	1965	9.92	1977	9.86	1832	10.6	1810	10.8	1802	10.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

Sun Studio compiler patches are available at
http://developers.sun.com/sunstudio/downloads/patches/ss12_patches.jsp
 The tested configuration included patch 124867-02, 127000-02,
 124863-02, 124861-04

Operating System Notes

Stack size set to unlimited with "ulimit -s unlimited"

Program threads were bound to processors with:

SUNW_MP_PROCBIND="1 3 5 7 9 11 13 15 17 19 21 23 25 27 29 31 33 35 37"

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems	SPECfp2006 =	23.6
Sun SPARC Enterprise M8000	SPECfp_base2006 =	20.9

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2008

Hardware Availability: Apr-2007

Software Availability: May-2008

Operating System Notes (Continued)

39 41 43 45 47 49 51 53 55 57 59 61 63"

Behavior of parallel threads was set with:

SUNW_MP_THR_IDLE=SPIN

SPIN specifies that an idle thread should spin while waiting at barrier or waiting for new parallel regions to work on.

The maximum number of threads a program can create was set with:

OMP_NUM_THREADS=32

System Tunables:

(/etc/system parameters)

maxphys=4194304

Defines the maximum size of I/O requests, in bytes.

maxpio=1024

Defines the maximum number of page I/O requests that can be queued by the paging system.

tune_t_fsflushr=4

Controls how many seconds elapse between runs of the page flush daemon, fsflush.

autoup=60

Causes pages older than the listed number of seconds to be written by fsflush.

bufhwm=3000

Memory byte limit for caching I/O buffers

segmap_percent=1

Set maximum percent memory for file system cache

Platform Notes

This result is measured on a Sun SPARC Enterprise M8000 Server. Note that the Sun SPARC Enterprise M8000 and Fujitsu SPARC Enterprise M8000 are electrically equivalent.

Memory is 8-way interleaved by filling all slots with the same capacity DIMMs.

Base Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun SPARC Enterprise M8000

SPECfp2006 = 23.6
SPECfp_base2006 = 20.9

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2008

Hardware Availability: Apr-2007

Software Availability: May-2008

Base Compiler Invocation (Continued)

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

Base Optimization Flags

C benchmarks:

```
-fast -xipo=2 -fma=fused -xpagesize=4M -xprefetch=latx:2 -xautopar  
-xreduction -xprefetch_level=3  
-xprefetch_auto_type=indirect_array_access
```

C++ benchmarks:

```
-library=stlport4 -fast -xipo=2 -fma=fused -xpatesize=4M  
-xprefetch=latx:2 -xautopar -xreduction -xprefetch_level=2  
-xalias_level=compatible
```

Fortran benchmarks:

```
-fast -xipo=2 -fma=fused -xpatesize=4M -xprefetch=latx:2 -xautopar  
-xreduction -xprefetch_level=2
```

Benchmarks using both Fortran and C:

```
-fast(cc) -fast(f90) -xipo=2 -fma=fused -xpatesize=4M  
-xprefetch=latx:2 -xautopar -xreduction -xprefetch_level=3  
-xprefetch_auto_type=indirect_array_access -xprefetch_level=2
```

Base Other Flags

C benchmarks:

-xjobs=64

C++ benchmarks:

-xjobs=64

Fortran benchmarks:

-xjobs=64

Benchmarks using both Fortran and C:

-xjobs=64



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun SPARC Enterprise M8000

SPECfp2006 = 23.6
SPECfp_base2006 = 20.9

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2008

Hardware Availability: Apr-2007

Software Availability: May-2008

Peak Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

Peak Optimization Flags

C benchmarks:

```
433.milc: -fast -xipo=2 -fma=fused -xpagesize=4M -xprefetch=latx:2  
          -xalias_level=std -xprefetch_level=3  
          -xprefetch_auto_type=indirect_array_access  
          -xalias_level=strong -xprefetch_level=2
```

```
470.lbm: -xprofile=collect:./feedback(pass 1)  
          -xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused  
          -xpagesize=4M -xprefetch=latx:2 -xalias_level=std  
          -xprefetch_level=3 -xprefetch_auto_type=indirect_array_access  
          -xarch=v8plusb -xprefetch_level=2 -xautopar -xreduction
```

```
482.sphinx3: -xprofile=collect:./feedback(pass 1)  
             -xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused  
             -xalias_level=std
```

C++ benchmarks:

```
444.namd: -library=stlport4 -fast -xipo=2 -fma=fused -xpagesize=4M  
          -xprefetch=latx:2 -xalias_level=compatible -xdepend
```

```
447.dealII: -library=stlport4 -xprofile=collect:./feedback(pass 1)  
            -xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused  
            -xalias_level=compatible -xdepend -xrestrict  
            -xprefetch=latx:4.5
```

```
450.soplex: -library=stlport4 -fast -xipo=2 -fma=fused -xpagesize=4M  
            -xprefetch=latx:2 -xdepend -xprefetch_level=2  
            -xprefetch_auto_type=indirect_array_access  
            -Qoption cg -Qlp-ol=1 -Qoption cg -Qlp-it=3  
            -Qoption cg -Qlp-imb=1 -Qoption iropt -Apf:pdl=3
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun SPARC Enterprise M8000

SPECfp2006 = 23.6
SPECfp_base2006 = 20.9

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2008

Hardware Availability: Apr-2007

Software Availability: May-2008

Peak Optimization Flags (Continued)

```
453.povray: -library=stlport4 -xprofile=collect:./feedback(pass 1)
             -xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused
             -xpagesize=4M -xprefetch=latx:2 -xalias_level=compatible
             -xdepend -xrestrict -xprefetch=latx:4.5
```

Fortran benchmarks:

```
410.bwaves: -fast -xipo=2 -fma=fused -xpagesize=512K -xprefetch=latx:2
             -xprefetch_level=2 -xautopar -xreduction
```

```
416.gamess: -fast -xipo=2 -fma=fused -xpagesize=4M -xprefetch=latx:2
             -xprefetch_level=2
```

```
434.zeusmp: basepeak = yes
```

```
437.leslie3d: -fast -xipo=2 -xautopar -xreduction -fma=fused
               -xprefetch_level=2 -xprefetch=latx:8.0
```

```
459.GemsFDTD: basepeak = yes
```

```
465.tonto: -xprofile=collect:./feedback(pass 1)
             -xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused
             -xpagesize=4M -xprefetch=latx:2 -xarch=v8plusa
             -xprefetch=latx:12 -lfast
```

Benchmarks using both Fortran and C:

```
435.gromacs: -xprofile=collect:./feedback(pass 1)
              -xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
              -xipo=2 -fma=fused -xalias_level=std
```

```
436.cactusADM: -fast(cc) -fast(f90) -xipo=2 -fma=fused -xpagesize=4M
                 -xprefetch=latx:2 -xalias_level=std -xprefetch_level=3
                 -xprefetch_auto_type=indirect_array_access -xautopar
                 -xreduction
```

```
454.calculix: -fast(cc) -fast(f90) -xipo=2 -fma=fused -xalias_level=std
```

```
481.wrf: basepeak = yes
```

Peak Other Flags

C benchmarks:

```
-xjobs=64
```

C++ benchmarks:

```
-xjobs=64
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems

SPECfp2006 = 23.6

Sun SPARC Enterprise M8000

SPECfp_base2006 = 20.9

CPU2006 license: 6

Test date: Mar-2008

Test sponsor: Sun Microsystems

Hardware Availability: Apr-2007

Tested by: Sun Microsystems

Software Availability: May-2008

Peak Other Flags (Continued)

Fortran benchmarks:

-x jobs=64

Benchmarks using both Fortran and C:

-x jobs=64

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-and-gccfss4.2.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-and-gccfss4.2.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.

Report generated on Tue Jul 22 15:27:52 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 19 March 2008.