



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp®2006 = 21.7

Lenovo SureServer R630 G7 (Intel Xeon E7440)

SPECfp_base2006 = 20.6

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon E7440
CPU Characteristics:
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip
CPU(s) orderable: 1,2,4 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 6 MB I+D on chip per chip, 3 MB shared / 2 cores

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16-60.0.21-smp
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: 1_cc_b_11.0.042, l_fc_b_11.0.042
Auto Parallel: Yes
File System: ReiserFS
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 21.7

Lenovo SureServer R630 G7 (Intel Xeon E7440)

SPECfp_base2006 = 20.6

CPU2006 license: 13

Test date: Sep-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008

Test sponsor: Intel Corporation

Tested by: Intel Corporation

L3 Cache: 16 MB I+D on chip per chip
 Other Cache: None
 Memory: 32 GB (16x2 GB Micron DDR2 5300F, CL5-5-5, 2 rank, ECC)
 Disk Subsystem: 73 GB Seagate SAS, 10K RPM
 Other Hardware: None

Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V8.1
 Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	272	50.0	271	50.1	273	49.9	272	50.0	273	49.9	271	50.1
416.gamess	1232	15.9	1231	15.9	1230	15.9	1069	18.3	1071	18.3	1071	18.3
433.milc	871	10.5	872	10.5	872	10.5	880	10.4	880	10.4	879	10.4
434.zeusmp	524	17.4	523	17.4	524	17.4	524	17.4	523	17.4	524	17.4
435.gromacs	447	16.0	446	16.0	446	16.0	442	16.1	443	16.1	443	16.1
436.cactusADM	85.8	139	85.8	139	85.9	139	86.5	138	87.0	137	86.8	138
437.leslie3d	649	14.5	649	14.5	647	14.5	649	14.5	649	14.5	647	14.5
444.namd	613	13.1	613	13.1	613	13.1	618	13.0	617	13.0	618	13.0
447.dealII	528	21.6	530	21.6	530	21.6	488	23.5	487	23.5	488	23.4
450.soplex	763	10.9	769	10.8	776	10.8	690	12.1	691	12.1	692	12.0
453.povray	270	19.7	271	19.7	273	19.5	230	23.1	230	23.2	231	23.0
454.calculix	462	17.8	464	17.8	464	17.8	434	19.0	449	18.4	434	19.0
459.GemsFDTD	400	26.5	401	26.5	400	26.5	387	27.4	388	27.3	387	27.4
465.tonto	738	13.3	752	13.1	740	13.3	541	18.2	544	18.1	542	18.1
470.lbm	413	33.3	410	33.5	406	33.8	413	33.3	410	33.5	406	33.8
481.wrf	692	16.1	693	16.1	693	16.1	693	16.1	694	16.1	694	16.1
482.sphinx3	838	23.3	836	23.3	836	23.3	836	23.3	836	23.3	836	23.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All benchmarks compiled in 64-bit mode except 450.soplex and 482.sphinx3, at peak, are compiled in 32-bit mode
 OMP_NUM_THREADS set to number of processors
 KMP_AFFINITY set to "physical,0"
 KMP_STACKSIZE set to 200M
 Hardware Prefetcher: Enabled
 Adjacent Cache Line Prefetcher: Enabled
 High Bandwidth Option: Disabled



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 21.7

Lenovo SureServer R630 G7 (Intel Xeon E7440)

SPECfp_base2006 = 20.6

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

C++ benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Fortran benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation	SPECfp2006 =	21.7
Lenovo SureServer R630 G7 (Intel Xeon E7440)	SPECfp_base2006 =	20.6
CPU2006 license: 13	Test date:	Sep-2008
Test sponsor: Intel Corporation	Hardware Availability:	Sep-2008
Tested by: Intel Corporation	Software Availability:	Nov-2008

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

```
482.sphinx3: /opt/intel/Compiler/11.0/042/bin/ia32/icc  
          -L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
          -I/opt/intel/Compiler/11.0/042/ipp/ia32/include
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/Compiler/11.0/042/bin/ia32/icpc  
          -L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
          -I/opt/intel/Compiler/11.0/042/ipp/ia32/include
```

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
        433.milc: -DSPEC_CPU_LP64  
        434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
        444.namd: -DSPEC_CPU_LP64  
        447.dealII: -DSPEC_CPU_LP64  
        453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
        470.lbm: -DSPEC_CPU_LP64  
        481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
          -no-prec-div -static -fno-alias
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 21.7

Lenovo SureServer R630 G7 (Intel Xeon E7440)

SPECfp_base2006 = 20.6

CPU2006 license: 13

Test date: Sep-2008

Test sponsor: Intel Corporation

Hardware Availability: Sep-2008

Tested by: Intel Corporation

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

470.lbm: basepeak = yes

482.sphinx3: -xsse4.1 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias -scalar-rep-
-opt-prefetch

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xsse4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -Obo -ansi-alias
-scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -Obo -opt-prefetch
-parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -opt-prefetch -parallel
-auto-ilp32

454.calculix: -xsse4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 21.7

Lenovo SureServer R630 G7 (Intel Xeon E7440)

SPECfp_base2006 = 20.6

CPU2006 license: 13

Test date: Sep-2008

Test sponsor: Intel Corporation

Hardware Availability: Sep-2008

Tested by: Intel Corporation

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

481.wrf: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.16.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.16.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 20:07:57 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 17 November 2008.