



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS P6T WS PRO workstation motherboard (Intel Core i7-965 Extreme Edition)

SPECfp®2006 = 39.3

SPECfp_base2006 = 37.4

CPU2006 license: 009016


Test sponsor: ASUSTeK Computer Inc.

Tested by: ASUSTeK Computer Inc.

Test date: Dec-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Core i7-965 Extreme Edition
 CPU Characteristics: Intel Turbo Boost Technology up to 3.46 GHz
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080930 Package ID: l_cproc_p_11.0.066, l_cprof_p_11.0.066
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS P6T WS PRO workstation motherboard (Intel Core i7-965 Extreme Edition)

SPECfp2006 = 39.3

SPECfp_base2006 = 37.4

CPU2006 license: 009016

Test sponsor: ASUSTeK Computer Inc.

Tested by: ASUSTeK Computer Inc.

Test date: Dec-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

L3 Cache: 8 MB I+D on chip per chip
 Other Cache: None
 Memory: 12 GB (6 x 2GB DDR3-1333 ECC, CL=9)
 Disk Subsystem: Hitachi HDT725050VLA360 500GB SATAII, 7200RPM
 Other Hardware: None

Peak Pointers: 32/64-bit
 Other Software: Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	153	88.7	<u>152</u>	<u>89.1</u>	152	89.3	<u>152</u>	<u>89.4</u>	152	89.5	152	89.1
416.gamess	835	23.4	<u>834</u>	<u>23.5</u>	833	23.5	<u>726</u>	<u>27.0</u>	<u>725</u>	<u>27.0</u>	725	27.0
433.milc	<u>235</u>	<u>39.1</u>	235	39.1	235	39.0	<u>238</u>	<u>38.5</u>	<u>239</u>	<u>38.4</u>	<u>239</u>	<u>38.5</u>
434.zeusmp	<u>234</u>	<u>38.9</u>	234	38.9	234	38.9	<u>234</u>	<u>38.9</u>	234	38.9	234	38.9
435.gromacs	310	23.0	<u>306</u>	<u>23.4</u>	305	23.4	<u>301</u>	<u>23.7</u>	<u>302</u>	<u>23.6</u>	303	23.6
436.cactusADM	127	93.9	<u>127</u>	<u>94.4</u>	126	94.6	<u>111</u>	<u>107</u>	110	109	<u>110</u>	<u>108</u>
437.leslie3d	271	34.7	272	34.5	<u>271</u>	<u>34.7</u>	271	34.7	272	34.5	<u>271</u>	<u>34.7</u>
444.namd	405	19.8	406	19.8	<u>405</u>	<u>19.8</u>	412	19.5	412	19.5	<u>412</u>	<u>19.5</u>
447.dealII	<u>327</u>	<u>35.0</u>	327	34.9	327	35.0	<u>296</u>	<u>38.6</u>	297	38.6	296	38.7
450.soplex	268	31.1	<u>268</u>	<u>31.1</u>	269	31.1	<u>260</u>	<u>32.0</u>	<u>260</u>	<u>32.0</u>	261	32.0
453.povray	180	29.6	182	29.3	<u>180</u>	<u>29.6</u>	<u>141</u>	<u>37.7</u>	<u>141</u>	<u>37.6</u>	141	37.6
454.calculix	304	27.1	<u>305</u>	<u>27.1</u>	306	27.0	<u>274</u>	<u>30.1</u>	285	28.9	<u>275</u>	<u>30.0</u>
459.GemsFDTD	<u>231</u>	<u>45.9</u>	231	45.9	231	45.9	<u>223</u>	<u>47.6</u>	223	47.6	223	47.5
465.tonto	<u>365</u>	<u>26.9</u>	365	27.0	366	26.9	<u>319</u>	<u>30.8</u>	<u>320</u>	<u>30.7</u>	322	30.6
470.lbm	<u>245</u>	<u>56.1</u>	245	56.1	245	56.0	<u>245</u>	<u>56.1</u>	245	56.1	245	56.0
481.wrf	<u>267</u>	<u>41.8</u>	267	41.9	267	41.8	<u>266</u>	<u>41.9</u>	267	41.9	<u>267</u>	<u>41.9</u>
482.sphinx3	<u>435</u>	<u>44.8</u>	435	44.8	437	44.6	<u>452</u>	<u>43.1</u>	<u>461</u>	<u>42.3</u>	451	43.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
 OMP_NUM_THREADS set to number of processors
 KMP_AFFINITY set to "physical,0"
 KMP_STACKSIZE set to 200M

Platform Notes

Tested systems can be used with formfactors.org ATX 2.2 spec
 PC Power and Cooling 600W power supply
 System was configured with ATI RV530LE discrete graphics card



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS P6T WS PRO workstation motherboard (Intel Core i7-965 Extreme Edition)

SPECfp2006 = 39.3

SPECfp_base2006 = 37.4

CPU2006 license: 009016

Test date: Dec-2008

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Nov-2008

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2008

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Fortran benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS P6T WS PRO workstation motherboard (Intel Core i7-965 Extreme Edition)

SPECfp2006 = 39.3

SPECfp_base2006 = 37.4

CPU2006 license: 009016

Test date: Dec-2008

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Nov-2008

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2008

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc

450.soplex: icpc -m32

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-fno-alias

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS P6T WS PRO workstation motherboard (Intel Core i7-965 Extreme Edition)

SPECfp2006 = 39.3

SPECfp_base2006 = 37.4

CPU2006 license: 009016

Test date: Dec-2008

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Nov-2008

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

C++ benchmarks:

```
444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -fno-alias -auto-ilp32
```

```
447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
            -unroll12 -ansi-alias -scalar-rep -opt-prefetch
```

```
450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
            -opt-malloc-options=3
```

```
453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
             -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
             -unroll14 -ansi-alias
```

Fortran benchmarks:

```
410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
             -parallel
```

```
416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
             -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
             -unroll12 -Ob0 -ansi-alias -scalar-rep-
```

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

```
459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
                -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
                -unroll12 -Ob0 -opt-prefetch -parallel
```

```
465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
             -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
             -unroll14 -auto
```

Benchmarks using both Fortran and C:

```
435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
              -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
              -opt-prefetch -auto-ilp32
```

```
436.cactusADM: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
                 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
                 -unroll12 -opt-prefetch -parallel -auto-ilp32
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS P6T WS PRO workstation motherboard (Intel Core i7-965 Extreme Edition)

SPECfp2006 = 39.3

SPECfp_base2006 = 37.4

CPU2006 license: 009016

Test date: Dec-2008

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Nov-2008

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.06.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.06.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 23:13:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 17 February 2009.