



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

**SPECfp®\_rate2006 = 173**

Motherboard X8DTE-F (Intel Xeon E5630, 2.53 GHz)

**SPECfp\_rate\_base2006 = 167**

CPU2006 license: 001176


Test date: May-2010

Test sponsor: Supermicro

Hardware Availability: Mar-2010

Tested by: Supermicro

Software Availability: Jan-2010



### Hardware

CPU Name: Intel Xeon E5630  
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz  
CPU MHz: 2533  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64)  
Compiler: Kernel 2.6.27.19-5-default  
Auto Parallel: Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 11.1  
File System: Build 20091130 Package ID: l\_cproc\_p\_11.1.064, l\_cprof\_p\_11.1.064  
System State: No  
ext3  
Run level 3 (multi-user)

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

**SPECfp\_rate2006 = 173**

Motherboard X8DTE-F (Intel Xeon E5630, 2.53 GHz)

**SPECfp\_rate\_base2006 = 167**

**CPU2006 license:** 001176

**Test date:** May-2010

**Test sponsor:** Supermicro

**Hardware Availability:** Mar-2010

**Tested by:** Supermicro

**Software Availability:** Jan-2010

L3 Cache: 12 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 48 GB (12 x 4 GB DDR3-1066 RDIMM, ECC, CL7)  
 Disk Subsystem: 1 x 500 GB SATA II, 7200 RPM  
 Other Hardware: None

Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	1334	163	<u>1335</u>	<u>163</u>	1336	163	8	656	166	<u>656</u>	<u>166</u>	655	166
416.gamess	16	<b>1832</b>	<b>171</b>	1845	170	1812	173	8	920	170	922	170	<b>922</b>	<b>170</b>
433.milc	16	<b>832</b>	<b>177</b>	832	177	832	177	16	830	177	<b>831</b>	<b>177</b>	831	177
434.zeusmp	16	733	199	<b>777</b>	<b>187</b>	779	187	16	733	199	<b>777</b>	<b>187</b>	779	187
435.gromacs	16	690	166	<b>699</b>	<b>163</b>	701	163	16	693	165	<b>689</b>	<b>166</b>	687	166
436.cactusADM	16	939	204	945	202	<b>943</b>	<b>203</b>	16	939	204	945	202	<b>943</b>	<b>203</b>
437.leslie3d	16	1361	110	1366	110	<b>1366</b>	<b>110</b>	8	658	114	<b>655</b>	<b>115</b>	654	115
444.namd	16	818	157	826	155	<b>819</b>	<b>157</b>	16	798	161	<b>798</b>	<b>161</b>	801	160
447.dealII	16	670	273	<b>672</b>	<b>273</b>	672	273	16	679	270	685	267	<b>680</b>	<b>269</b>
450.soplex	16	1042	128	<b>1043</b>	<b>128</b>	1043	128	8	493	135	<b>488</b>	<b>137</b>	488	137
453.povray	16	365	233	<b>364</b>	<b>234</b>	364	234	16	<b>302</b>	<b>281</b>	301	283	304	280
454.calculix	16	<b>640</b>	<b>206</b>	642	206	640	206	16	<b>640</b>	<b>206</b>	642	206	640	206
459.GemsFDTD	16	1655	103	1646	103	<b>1652</b>	<b>103</b>	8	<b>780</b>	<b>109</b>	780	109	<b>785</b>	108
465.tonto	16	824	191	<b>822</b>	<b>192</b>	820	192	16	778	202	<b>771</b>	<b>204</b>	767	205
470.lbm	16	2182	101	2184	101	<b>2184</b>	<b>101</b>	8	1016	108	<b>1017</b>	<b>108</b>	1017	108
481.wrf	16	944	189	923	194	<b>944</b>	<b>189</b>	16	944	189	923	194	<b>944</b>	<b>189</b>
482.sphinx3	16	<b>1743</b>	<b>179</b>	1742	179	1745	179	16	<b>1629</b>	<b>191</b>	1629	191	1630	191

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
 numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stack size to unlimited prior to run

## Platform Notes

Fan speed set to Full Speed in BIOS Setup.  
 As tested, the system used a Supermicro CSE-743TQ-865B chassis.  
 The chassis is configured with a PWS-865-PQ power supply, 2 SNK-P0038P heatsinks,  
 as well as 4 FAN-0074L and 2 FAN-0082L4 cooling fans.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro**

Motherboard X8DTE-F (Intel Xeon E5630, 2.53 GHz)

**SPECfp\_rate2006 = 173**

**SPECfp\_rate\_base2006 = 167**

**CPU2006 license:** 001176

**Test date:** May-2010

**Test sponsor:** Supermicro

**Hardware Availability:** Mar-2010

**Tested by:** Supermicro

**Software Availability:** Jan-2010

## General Notes

Binaries were compiled on SLES 10 with Binutils 2.18.50.0.7.20080502

## Base Compiler Invocation

C benchmarks:

  icc -m64

C++ benchmarks:

  icpc -m64

Fortran benchmarks:

  ifort -m64

Benchmarks using both Fortran and C:

  icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
  433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
  444.namd: -DSPEC\_CPU\_LP64  
  447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
  465.tonto: -DSPEC\_CPU\_LP64  
  470.lbm: -DSPEC\_CPU\_LP64  
  481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

  -xSSE4.2 -ipo -O3 -no-prec-div -static

C++ benchmarks:

  -xSSE4.2 -ipo -O3 -no-prec-div -static

Fortran benchmarks:

  -xSSE4.2 -ipo -O3 -no-prec-div -static

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard X8DTE-F (Intel Xeon E5630, 2.53 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

**SPECfp\_rate2006 = 173**

**SPECfp\_rate\_base2006 = 167**

Test date: May-2010

Hardware Availability: Mar-2010

Software Availability: Jan-2010

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Motherboard X8DTE-F (Intel Xeon E5630, 2.53 GHz)

**SPECfp\_rate2006 = 173**

**CPU2006 license:** 001176

**Test date:** May-2010

**Test sponsor:** Supermicro

**Hardware Availability:** Mar-2010

**Tested by:** Supermicro

**Software Availability:** Jan-2010

## Peak Optimization Flags (Continued)

433.milc: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -opt-prefetch

470.lbm: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3 -ansi-alias -auto-ilp32

482.sphinx3: -xsse4 .2 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealII: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias -scalar-rep-

450.soplex: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3

453.povray: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xsse4 .2 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: -xsse4 .2 -ipo -O3 -no-prec-div -static

459.GemsFDTD: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0

465.tonto: -xsse4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -auto -inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard X8DTE-F (Intel Xeon E5630, 2.53 GHz)

**SPECfp\_rate2006 = 173**

CPU2006 license: 001176

Test date: May-2010

Test sponsor: Supermicro

Hardware Availability: Mar-2010

Tested by: Supermicro

Software Availability: Jan-2010

## Peak Optimization Flags (Continued)

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100804.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100804.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 12:02:29 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 17 August 2010.