



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp®_rate2006 = 130

Intel DH87MC motherboard (Intel Core i5-4570)

SPECfp_rate_base2006 = 130

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2013

Hardware Availability: Jun-2013

Software Availability: Apr-2013



Hardware

CPU Name: Intel Core i5-4570
 CPU Characteristics: Intel Turbo Boost Technology up to 3.6 GHz
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Microsoft Windows 8 Pro
 6.2.9200 N/A Build 9200
 Compiler: C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows;
 Fortran: Version 13.1.1.171 of Intel Fortran Studio XE for Windows;
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
 Auto Parallel: No

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = **130**

Intel DH87MC motherboard (Intel Core i5-4570)

SPECfp_rate_base2006 = **130**

CPU2006 license: 13

Test date: Jul-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

L3 Cache: 6 MB I+D on chip per chip
 Other Cache: None
 Memory: 8 GB (2 x 4 GB 2Rx8 PC3-12800U-9)
 Disk Subsystem: 1 TB Seagate SATA, 7200 RPM
 Other Hardware: None

File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 10.0 from <http://www.microquill.com/>

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	467	116	<u>466</u>	<u>117</u>	465	117	4	467	116	<u>466</u>	<u>117</u>	465	117
416.gamess	4	534	147	<u>534</u>	<u>147</u>	533	147	4	534	147	<u>534</u>	<u>147</u>	533	147
433.milc	4	331	111	330	111	<u>330</u>	<u>111</u>	4	331	111	330	111	<u>330</u>	<u>111</u>
434.zeusmp	4	252	144	<u>254</u>	<u>143</u>	254	143	4	252	144	<u>254</u>	<u>143</u>	254	143
435.gromacs	4	180	159	180	158	<u>180</u>	<u>159</u>	4	180	159	180	158	<u>180</u>	<u>159</u>
436.cactusADM	4	<u>260</u>	<u>184</u>	260	184	317	151	4	<u>260</u>	<u>184</u>	260	184	317	151
437.leslie3d	4	<u>463</u>	<u>81.2</u>	464	81.2	459	82.0	4	<u>463</u>	<u>81.2</u>	464	81.2	459	82.0
444.namd	4	297	108	<u>296</u>	<u>108</u>	296	108	4	296	108	296	108	<u>296</u>	<u>108</u>
447.dealII	4	235	195	<u>244</u>	<u>188</u>	246	186	4	235	195	<u>244</u>	<u>188</u>	246	186
450.soplex	4	<u>416</u>	<u>80.4</u>	423	78.8	410	81.2	4	411	81.2	409	81.6	<u>411</u>	<u>81.2</u>
453.povray	4	101	212	101	210	<u>101</u>	<u>212</u>	4	<u>95.2</u>	<u>224</u>	94.0	226	95.5	223
454.calculix	4	<u>194</u>	<u>170</u>	193	171	194	170	4	<u>194</u>	<u>170</u>	193	171	194	170
459.GemsFDTD	4	<u>612</u>	<u>69.2</u>	612	69.2	611	69.6	4	<u>612</u>	<u>69.2</u>	612	69.2	611	69.6
465.tonto	4	<u>300</u>	<u>131</u>	301	131	299	132	4	285	138	<u>286</u>	<u>138</u>	286	138
470.lbm	4	381	144	<u>381</u>	<u>144</u>	381	144	4	381	144	<u>381</u>	<u>144</u>	381	144
481.wrf	4	<u>328</u>	<u>136</u>	328	136	337	132	4	<u>328</u>	<u>136</u>	328	136	337	132
482.sphinx3	4	<u>658</u>	<u>118</u>	667	117	622	125	4	<u>658</u>	<u>118</u>	667	117	622	125

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 13.1 was set up to generate 64-bit binaries with the command:
 "ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

Submit Notes

Processes were bound to specific processors using the start command with the /affinity switch. The config file option 'submit' was used to generate the affinity mask for each process.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 130

Intel DH87MC motherboard (Intel Core i5-4570)

SPECfp_rate_base2006 = 130

CPU2006 license: 13

Test date: Jul-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Platform Notes

Sysinfo program C:\Users\PECA_W~1\Desktop\CPU200~1.APR/Docs/sysinfo
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on HSW_9200 Sat Jul 13 19:39:17 2013

This section contains SUT (System Under Test) info as seen by
some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

OS Name : Microsoft Windows 8 Pro
OS Version : 6.2.9200 N/A Build 9200
System Manufacturer: INTEL_
System Model : DH87MC_
Processor(s) : 1 Processor(s) Installed.
 [01]: Intel64 Family 6 Model 60 Stepping 3 GenuineIntel ~3201 Mhz
BIOS Version : Intel Corp. MCH8710H.86A.0043.2013.0412.2225, 4/12/2013
Total Physical Memory: 7,864 MB

Trying 'wmic cpu get /value'

DeviceID : CPU0
L2CacheSize : 1024
L3CacheSize : 6144
MaxClockSpeed : 3201
Name : Intel(R) Core(TM) i5-4570 CPU @ 3.20GHz
NumberOfCores : 4
NumberOfLogicalProcessors: 4

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

icl -Qvc10 -Qstd=c99

C++ benchmarks:

icl -Qvc10

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 130

Intel DH87MC motherboard (Intel Core i5-4570)

SPECfp_rate_base2006 = 130

CPU2006 license: 13

Test date: Jul-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc10 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
 416.gamess: -DSPEC_CPU_P64
 433.milc: -DSPEC_CPU_P64
 434.zeusmp: -DSPEC_CPU_P64
 435.gromacs: -DSPEC_CPU_P64
 436.cactusADM: -DSPEC_CPU_P64 /names:lowercase /assume:underscore
 437.leslie3d: -DSPEC_CPU_P64
 444.namd: -DSPEC_CPU_P64 /TP
 447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
 -Qoption,cpp,--ms_incompat_treatment_of_commas_in_macros
 450.soplex: -DSPEC_CPU_P64
 453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_NEED_INVHYP -DNEED_INVHYP
 454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER /names:lowercase
 459.GemsFDTD: -DSPEC_CPU_P64
 465.tonto: -DSPEC_CPU_P64
 470.lbm: -DSPEC_CPU_P64
 481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
/F1000000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 130

Intel DH87MC motherboard (Intel Core i5-4570)

SPECfp_rate_base2006 = 130

CPU2006 license: 13

Test date: Jul-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Peak Compiler Invocation

C benchmarks:

icl -Qvc10 -Qstd=c99

C++ benchmarks:

icl -Qvc10

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc10 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
shlW64M.lib -link /FORCE:MULTIPLE

447.dealIII: basepeak = yes

450.soplex: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

453.povray: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
/F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 130

Intel DH87MC motherboard (Intel Core i5-4570)

SPECfp_rate_base2006 = 130

CPU2006 license: 13

Test date: Jul-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Peak Optimization Flags (Continued)

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 16:10:17 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 September 2013.