



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6700 APU
with Radeon HD Graphics)

SPECfp®2006 = 33.4

SPECfp_base2006 = 31.9

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2014

Hardware Availability: Aug-2013

Software Availability: Apr-2013



Hardware

CPU Name: AMD A10-6700
 CPU Characteristics: AMD Turbo CORE technology up to 4.30 GHz
 CPU MHz: 3700
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 128 KB I on chip per chip, 64 KB I shared / 2 cores; 16 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip, 2 MB shared / 2 cores

Software

Operating System: Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows;
 Fortran: Version 13.1.1.171 of Intel Fortran Studio XE for Windows;
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
 Auto Parallel: Yes

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6700 APU
with Radeon HD Graphics)

SPECfp2006 = 33.4

SPECfp_base2006 = 31.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2014

Hardware Availability: Aug-2013

Software Availability: Apr-2013

L3 Cache:	None	File System:	NTFS
Other Cache:	None	System State:	Default
Memory:	4 GB (2 x 2 GB 1Rx8 PC3-12800U-11)	Base Pointers:	32/64-bit
Disk Subsystem:	250 GB Seagate SATA HDD, 7200 RPM	Peak Pointers:	32/64-bit
Other Hardware:	None	Other Software:	SmartHeap Library Version 10.0 from http://www.microquill.com/

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	223	61.1	223	60.9	<u>223</u>	<u>60.9</u>	223	61.1	223	60.9	<u>223</u>	<u>60.9</u>
416.gamess	<u>971</u>	<u>20.2</u>	974	20.1	968	20.2	<u>737</u>	<u>26.6</u>	<u>729</u>	<u>26.9</u>	726	27.0
433.milc	276	33.2	277	33.2	<u>277</u>	<u>33.2</u>	<u>276</u>	33.2	277	33.2	<u>277</u>	<u>33.2</u>
434.zeusmp	<u>241</u>	<u>37.8</u>	241	37.8	240	37.9	<u>241</u>	<u>37.8</u>	241	37.8	240	37.9
435.gromacs	261	27.4	<u>261</u>	<u>27.4</u>	261	27.3	261	27.4	<u>261</u>	<u>27.4</u>	261	27.3
436.cactusADM	<u>225</u>	<u>53.2</u>	225	53.1	224	53.3	<u>225</u>	<u>53.2</u>	225	53.1	224	53.3
437.leslie3d	<u>367</u>	<u>25.6</u>	367	25.6	366	25.7	<u>367</u>	<u>25.6</u>	367	25.6	366	25.7
444.namd	372	21.6	371	21.6	<u>372</u>	<u>21.6</u>	365	22.0	<u>365</u>	<u>22.0</u>	365	22.0
447.dealII	267	42.9	267	42.8	<u>267</u>	<u>42.9</u>	267	42.9	267	42.8	<u>267</u>	<u>42.9</u>
450.soplex	<u>392</u>	<u>21.3</u>	391	21.3	393	21.2	<u>392</u>	<u>21.3</u>	391	21.3	393	21.2
453.povray	178	29.9	<u>178</u>	<u>29.9</u>	179	29.8	157	33.8	157	33.9	<u>157</u>	<u>33.9</u>
454.calculix	<u>277</u>	<u>29.7</u>	277	29.8	277	29.7	<u>277</u>	<u>29.7</u>	277	29.8	277	29.7
459.GemsFDTD	405	26.2	<u>404</u>	<u>26.3</u>	404	26.3	405	26.2	<u>404</u>	<u>26.3</u>	404	26.3
465.tonto	538	18.3	537	18.3	<u>537</u>	<u>18.3</u>	<u>391</u>	<u>25.2</u>	388	25.4	392	25.1
470.lbm	159	86.3	<u>157</u>	<u>87.6</u>	155	88.5	<u>159</u>	<u>86.3</u>	<u>157</u>	<u>87.6</u>	155	88.5
481.wrf	351	31.9	<u>350</u>	<u>31.9</u>	350	31.9	<u>351</u>	<u>31.9</u>	<u>350</u>	<u>31.9</u>	350	31.9
482.sphinx3	712	27.4	708	27.5	<u>711</u>	<u>27.4</u>	712	27.4	708	27.5	<u>711</u>	<u>27.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 13.1 was set up to generate 64-bit binaries with the command:

"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

Platform Notes

Sysinfo program C:\SPEC13.1\Docs\sysinfo
\$Rev: 6775 \$ \$Date::: 2011-08-16 #\\$ \8787f7622badcf24e01c368b1db4377c
running on F2A85MPRO Sat Jan 18 18:20:36 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6700 APU
with Radeon HD Graphics)

SPECfp2006 = 33.4

SPECfp_base2006 = 31.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2014

Hardware Availability: Aug-2013

Software Availability: Apr-2013

Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name      : Microsoft Windows 7 Enterprise
OS Version   : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model  : System Product Name
Processor(s)  : 1 Processor(s) Installed.
                 [01]: AMD64 Family 21 Model 19 Stepping 1 AuthenticAMD ~3700 Mhz
BIOS Version  : American Megatrends Inc. 6303, 8/13/2013
Total Physical Memory: 3,271 MB
```

```
Trying 'wmic cpu get /value'
DeviceID     : CPU0
L2CacheSize  : 4096
L3CacheSize  : 0
MaxClockSpeed: 3700
Name         : AMD A10-6700 APU with Radeon(tm) HD Graphics
NumberOfCores: 2
NumberOfLogicalProcessors: 4
```

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
Micron MT8JTF25664AZ-1G6 Series Memory DIMMs

General Notes

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

 icl -Qvc10 -Qstd=c99

C++ benchmarks:

 icl -Qvc10

Fortran benchmarks:

 ifort

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6700 APU
with Radeon HD Graphics)

SPECfp2006 = 33.4

SPECfp_base2006 = 31.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2014

Hardware Availability: Aug-2013

Software Availability: Apr-2013

Base Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

```
icl -Qvc10 -Qstd=c99 ifort
```

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
  433.milc: -DSPEC_CPU_P64
  434.zeusmp: -DSPEC_CPU_P64
  435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
  437.leslie3d: -DSPEC_CPU_P64
    444.namd: -DSPEC_CPU_P64 /TP
  447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
    -Qoption,cpp,--ms_incompat_treatment_of_commas_in_macros
  450.soplex: -DSPEC_CPU_P64
  453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_NEED_INVHYP -DNEED_INVHYP
  454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
  465.tonto: -DSPEC_CPU_P64
    470.lbm: -DSPEC_CPU_P64
      481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
  482.sphinx3: -DSPEC_CPU_P64
```

Base Optimization Flags

C benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qauto-ilp32 /F1000000000
```

C++ benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F1000000000 shlW64M.lib
  -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000
```

Benchmarks using both Fortran and C:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qauto-ilp32 /F1000000000
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6700 APU
with Radeon HD Graphics)

SPECfp2006 = 33.4

SPECfp_base2006 = 31.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2014

Hardware Availability: Aug-2013

Software Availability: Apr-2013

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc10 -Qstd=c99 ifort
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: basepeak = yes
```

C++ benchmarks:

```
444.namd: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
           -Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
           shlw64M.lib               -link /FORCE:MULTIPLE
```

```
447.dealII: basepeak = yes
```

```
450.soplex: basepeak = yes
```

```
453.povray: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll14 -Qansi-alias -Qauto-ilp32
            /F1000000000 shlw64M.lib               -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
410.bwaves: basepeak = yes
```

```
416.gamess: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll12 -Ob0 -Qansi-alias
            -Qscalar-rep- /F1000000000
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6700 APU
with Radeon HD Graphics)

SPECfp2006 = 33.4

SPECfp_base2006 = 31.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2014

Hardware Availability: Aug-2013

Software Availability: Apr-2013

Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll14 -Qauto -Qinline-calloc
/F10000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.20130924.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.20130924.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Aug 12 15:06:17 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 July 2014.