



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6800K APU with Radeon HD Graphics)

SPECfp<sup>®</sup>2006 = 34.5

SPECfp\_base2006 = 33.1

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2013

Hardware Availability: Jun-2013

Software Availability: Apr-2013



**Hardware**

CPU Name: AMD A10-6800K  
 CPU Characteristics: AMD Turbo CORE technology up to 4.40 GHz  
 CPU MHz: 4100  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 128 KB I on chip per chip, 64 KB I shared / 2 cores; 16 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip, 2 MB shared / 2 cores

Continued on next page

**Software**

Operating System: Microsoft Windows 7 Ultimate 6.1.7601 Service Pack 1 Build 7601  
 Compiler: C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows;  
 Fortran: Version 13.1.1.171 of Intel Fortran Studio XE for Windows;  
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1  
 Auto Parallel: Yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6800K APU with Radeon HD Graphics)

SPECfp2006 = 34.5

SPECfp\_base2006 = 33.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2013

Hardware Availability: Jun-2013

Software Availability: Apr-2013

L3 Cache: None  
Other Cache: None  
Memory: 4 GB (2 x 2 GB 1Rx8 PC3-12800U-11)  
Disk Subsystem: 250 GB Seagate SATA HDD, 7200 RPM  
Other Hardware: None

File System: NTFS  
System State: Default  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: SmartHeap Library Version 10.0 from <http://www.microquill.com/>

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	218	62.4	215	63.1	<u>217</u>	<u>62.7</u>	218	62.4	215	63.1	<u>217</u>	<u>62.7</u>
416.gamess	908	21.6	911	21.5	<u>909</u>	<u>21.5</u>	<u>710</u>	<u>27.6</u>	713	27.5	709	27.6
433.milc	<u>268</u>	<u>34.3</u>	267	34.3	268	34.3	<u>268</u>	<u>34.3</u>	267	34.3	268	34.3
434.zeusmp	231	39.4	<u>231</u>	<u>39.4</u>	231	39.4	231	39.4	<u>231</u>	<u>39.4</u>	231	39.4
435.gromacs	<u>255</u>	<u>28.0</u>	255	28.1	255	28.0	<u>255</u>	<u>28.0</u>	255	28.1	255	28.0
436.cactusADM	213	56.1	<u>216</u>	<u>55.3</u>	216	55.3	213	56.1	<u>216</u>	<u>55.3</u>	216	55.3
437.leslie3d	<u>354</u>	<u>26.6</u>	353	26.6	354	26.6	<u>354</u>	<u>26.6</u>	353	26.6	354	26.6
444.namd	362	22.1	<u>362</u>	<u>22.1</u>	363	22.1	356	22.5	356	22.5	<u>356</u>	<u>22.5</u>
447.dealII	259	44.2	259	44.1	<u>259</u>	<u>44.2</u>	259	44.2	259	44.1	<u>259</u>	<u>44.2</u>
450.soplex	378	22.0	380	21.9	<u>379</u>	<u>22.0</u>	378	22.0	380	21.9	<u>379</u>	<u>22.0</u>
453.povray	173	30.7	<u>174</u>	<u>30.6</u>	174	30.6	153	34.9	<u>153</u>	<u>34.7</u>	153	34.7
454.calculix	<u>272</u>	<u>30.3</u>	272	30.3	272	30.4	<u>272</u>	<u>30.3</u>	272	30.3	272	30.4
459.GemsFDTD	391	27.1	<u>390</u>	<u>27.2</u>	390	27.2	391	27.1	<u>390</u>	<u>27.2</u>	390	27.2
465.tonto	498	19.8	497	19.8	<u>498</u>	<u>19.8</u>	377	26.1	<u>378</u>	<u>26.0</u>	378	26.0
470.lbm	154	89.3	<u>153</u>	<u>90.0</u>	153	90.0	154	89.3	<u>153</u>	<u>90.0</u>	153	90.0
481.wrf	<u>330</u>	<u>33.9</u>	328	34.1	330	33.8	<u>330</u>	<u>33.9</u>	328	34.1	330	33.8
482.sphinx3	686	28.4	687	28.4	<u>686</u>	<u>28.4</u>	686	28.4	687	28.4	<u>686</u>	<u>28.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler 13.1 was set up to generate 64-bit binaries with the command:  
"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

## Platform Notes

Sysinfo program C:\SPEC13.1\Docs\sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c  
running on Clt14DAE908A2BC Thu Sep 19 01:24:13 2013

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6800K APU with Radeon HD Graphics)

**SPECfp2006 = 34.5**

**SPECfp\_base2006 = 33.1**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Sep-2013

**Hardware Availability:** Jun-2013

**Software Availability:** Apr-2013

## Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

```
OS Name       : Microsoft Windows 7 Ultimate
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model   : System Product Name
Processor(s)  : 1 Processor(s) Installed.
               [01]: AMD64 Family 21 Model 19 Stepping 1 AuthenticAMD ~4100 Mhz
BIOS Version  : American Megatrends Inc. 6105, 5/8/2013
Total Physical Memory: 3,111 MB
```

Trying 'wmic cpu get /value'

```
DeviceID      : CPU0
L2CacheSize   : 4096
L3CacheSize   : 0
MaxClockSpeed : 4100
Name          : AMD A10-6800K APU with Radeon(tm) HD Graphics
NumberOfCores : 2
NumberOfLogicalProcessors: 4
```

(End of data from sysinfo program)

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply  
Micron MT8JTF25664AZ-1G6 Series Memory DIMMs

## General Notes

OMP\_NUM\_THREADS set to number of processors cores  
KMP\_AFFINITY set to granularity=fine,scatter  
Binaries compiled on a system with 1x Intel Core i7-860 CPU  
+ 8GB memory using Windows 7 Enterprise 64-bit

## Base Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Fortran benchmarks:

```
ifort
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6800K APU with Radeon HD Graphics)

**SPECfp2006 = 34.5**

**SPECfp\_base2006 = 33.1**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Sep-2013

**Hardware Availability:** Jun-2013

**Software Availability:** Apr-2013

## Base Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

```
icl -Qvc10 -Qstd=c99 ifort
```

## Base Portability Flags

```

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-Qoption,cpp,--ms_incompat_treatment_of_commas_in_macros
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_NEED_INVHYP -DNEED_INVHYP
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

```

## Base Optimization Flags

C benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qauto-ilp32 /F1000000000
```

C++ benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F1000000000 sh1W64M.lib
-link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000
```

Benchmarks using both Fortran and C:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qauto-ilp32 /F1000000000
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6800K APU with Radeon HD Graphics)

SPECfp2006 = 34.5

SPECfp\_base2006 = 33.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2013

Hardware Availability: Jun-2013

Software Availability: Apr-2013

## Peak Compiler Invocation

C benchmarks:

icl -Qvc10 -Qstd=c99

C++ benchmarks:

icl -Qvc10

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc10 -Qstd=c99 ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: /arch:AVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000  
sh1W64M.lib -link /FORCE:MULTIPLE

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: /arch:AVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias -Qauto-ilp32  
/F1000000000 sh1W64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: /arch:AVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias  
-Qscalar-rep- /F1000000000

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**

(Test Sponsor: Intel Corporation)

ASUS F2A85-M PRO motherboard (AMD A10-6800K APU with Radeon HD Graphics)

**SPECfp2006 = 34.5**

**SPECfp\_base2006 = 33.1**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Sep-2013

**Hardware Availability:** Jun-2013

**Software Availability:** Apr-2013

## Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

```
465.tonto: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
           -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc
           /F1000000000
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.20130924.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.20130924.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Aug 12 15:06:17 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 15 July 2014.