



SPEC[®] CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

HITACHI

SPECfp[®]_rate2006 = Not Run

BladeSymphony BS2500 (Intel Xeon E7-8890 v3)

SPECfp_rate_base2006 = 1960

CPU2006 license: 35


Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014



Hardware

CPU Name: Intel Xeon E7-8890 v3
 CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz
 CPU MHz: 2500
 FPU: Integrated
 CPU(s) enabled: 72 cores, 4 chips, 18 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2,3,4 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.6 (Santiago)
 2.6.32-504.el6.x86_64
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
 Auto Parallel: No
 File System: ext4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = Not Run

BladeSymphony BS2500 (Intel Xeon E7-8890 v3)

SPECfp_rate_base2006 = 1960

CPU2006 license: 35

Test date: May-2015

Test sponsor: HITACHI

Hardware Availability: Jun-2015

Tested by: HITACHI

Software Availability: Oct-2014

L3 Cache: 45 MB I+D on chip per chip
 Other Cache: None
 Memory: 1 TB (64 x 16 GB 2Rx4 PC4-2133P-R, running at 1600 MHz)
 Disk Subsystem: 2 x 300 GB SAS, 15000 RPM, RAID1
 Other Hardware: None

System State: Run level 5
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: none

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	144	1282	1530	<u>1282</u>	<u>1530</u>	1285	1520							
416.gamess	144	<u>1151</u>	<u>2450</u>	1137	2480	1153	2440							
433.milc	144	917	1440	<u>917</u>	<u>1440</u>	919	1440							
434.zeusmp	144	610	2150	601	2180	<u>601</u>	<u>2180</u>							
435.gromacs	144	374	2750	<u>375</u>	<u>2740</u>	377	2730							
436.cactusADM	144	696	2470	<u>694</u>	<u>2480</u>	693	2480							
437.leslie3d	144	1296	1040	<u>1297</u>	<u>1040</u>	1297	1040							
444.namd	144	<u>559</u>	<u>2060</u>	563	2050	557	2070							
447.dealII	144	<u>439</u>	<u>3750</u>	439	3750	442	3730							
450.soplex	144	1178	1020	1185	1010	<u>1182</u>	<u>1020</u>							
453.povray	144	<u>236</u>	<u>3250</u>	238	3220	235	3260							
454.calculix	144	<u>387</u>	<u>3070</u>	387	3070	388	3060							
459.GemsFDTD	144	1559	980	<u>1561</u>	<u>979</u>	1562	978							
465.tonto	144	<u>616</u>	<u>2300</u>	617	2300	614	2310							
470.lbm	144	1008	1960	<u>1010</u>	<u>1960</u>	1010	1960							
481.wrf	144	880	1830	<u>882</u>	<u>1820</u>	882	1820							
482.sphinx3	144	1568	1790	<u>1580</u>	<u>1780</u>	1594	1760							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = Not Run

BladeSymphony BS2500 (Intel Xeon E7-8890 v3)

SPECfp_rate_base2006 = 1960

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014

Platform Notes

BIOS configuration:

C-State = Disable
C1 Enhanced Mode = Disable
Active Energy Manager = Capping Disabled
Platform Controlled Type = Maximum Performance
Memory Power Management = Disable
Patrol Scrub = Disable

Sysinfo program /home/cpu2006/config/sysinfo.rev6818
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191
running on localhost Wed May 13 23:40:46 2015

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E7-8890 v3 @ 2.50GHz
4 "physical id"s (chips)
144 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores : 18
siblings : 36
physical 0: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 1: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 2: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 3: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
cache size : 46080 KB

From /proc/meminfo
MemTotal: 1058391176 kB
HugePages_Total: 0
Hugepagesize: 2048 kB

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.6 (Santiago)

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.6 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.6 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

uname -a:
Linux localhost 2.6.32-504.el6.x86_64 #1 SMP Tue Sep 16 01:56:35 EDT 2014
x86_64 x86_64 x86_64 GNU/Linux

run-level 5 May 13 16:10

SPEC is set to: /home/cpu2006
Filesystem Type Size Used Avail Use% Mounted on
Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = Not Run

BladeSymphony BS2500 (Intel Xeon E7-8890 v3)

SPECfp_rate_base2006 = 1960

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014

Platform Notes (Continued)

```
/dev/mapper/vg_rhel6-lv_home
ext4 221G 66G 144G 32% /home
```

Additional information from dmidecode:

BIOS HITACHI 09-07 04/28/2015

Memory:

32x NO DIMM Unknown

64x Samsung M393A2G40DB0-CPB 16 GB 1600 MHz 2 rank

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

```
LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"
```

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

```
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
```

Filesystem page cache cleared with:

```
echo 1> /proc/sys/vm/drop_caches
```

runspec command invoked through numactl i.e.:

```
numactl --interleave=all runspec <etc>
```

BladeSymphony BS520X, BladeSymphony BS2500 and Hitachi Compute Blade 520X are electronically equivalent.

The results have been measured on a Hitachi Compute Blade 520X.

Base Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64

416.gamess: -DSPEC_CPU_LP64

433.milc: -DSPEC_CPU_LP64

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 4



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = Not Run

BladeSymphony BS2500 (Intel Xeon E7-8890 v3)

SPECfp_rate_base2006 = 1960

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014

Base Portability Flags (Continued)

```

434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

C++ benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

Fortran benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

```

Benchmarks using both Fortran and C:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.html>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.20150602.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.xml>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.20150602.xml>



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

HITACHI

SPECfp_rate2006 = Not Run

BladeSymphony BS2500 (Intel Xeon E7-8890 v3)

SPECfp_rate_base2006 = 1960

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2015

Hardware Availability: Jun-2015

Software Availability: Oct-2014

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Jun 30 12:00:58 2015 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 June 2015.