



SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp®_rate2006 = 674

HPC HD S2600KPR (Intel Xeon E5-2630 v4, 2.2 GHz)

SPECfp_rate_base2006 = 659

CPU2006 license: 4204


Test date: Jun-2016

Test sponsor: M Computers s.r.o.

Hardware Availability: Mar-2016

Tested by: M Computers s.r.o.

Software Availability: Feb-2016



Hardware

CPU Name: Intel Xeon E5-2630 v4
 CPU Characteristics: Intel Turbo Boost Technology up to 3.10 GHz
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: CentOS Linux release 7.2.1511 (Core)
 3.10.0-327.18.2.el7.x86_64
 Compiler: C/C++: Version 16.0.2.181 of Intel C++ Studio XE for Linux
 Auto Parallel: No
 File System: xfs
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp_rate2006 = 674

HPC HD S2600KPR (Intel Xeon E5-2630 v4, 2.2 GHz)

SPECfp_rate_base2006 = 659

CPU2006 license: 4204

Test date: Jun-2016

Test sponsor: M Computers s.r.o.

Hardware Availability: Mar-2016

Tested by: M Computers s.r.o.

Software Availability: Feb-2016

L3 Cache: 25 MB I+D on chip per chip
Other Cache: None
Memory: 128 GB (8 x 16 GB 2Rx4 PC4-2133T-R)
Disk Subsystem: 420 GB SATA SSHD
Other Hardware: None

Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	40	981	554	980	555	<u>981</u>	<u>554</u>	40	981	554	980	555	<u>981</u>	<u>554</u>
416.gamess	40	<u>1161</u>	<u>675</u>	1160	675	1166	672	40	<u>1127</u>	<u>695</u>	1133	691	1126	695
433.milc	40	680	540	<u>680</u>	<u>540</u>	680	540	40	680	540	<u>680</u>	<u>540</u>	680	540
434.zeusmp	40	464	784	<u>465</u>	<u>783</u>	470	775	40	464	784	<u>465</u>	<u>783</u>	470	775
435.gromacs	40	<u>345</u>	<u>829</u>	346	826	344	829	40	328	872	<u>328</u>	<u>870</u>	332	860
436.cactusADM	40	535	893	<u>536</u>	<u>893</u>	536	892	40	535	893	<u>536</u>	<u>893</u>	536	892
437.leslie3d	40	973	387	970	388	<u>971</u>	<u>387</u>	40	973	387	970	388	<u>971</u>	<u>387</u>
444.namd	40	592	542	595	539	<u>595</u>	<u>540</u>	40	<u>589</u>	<u>545</u>	588	545	589	545
447.dealII	40	<u>419</u>	<u>1090</u>	422	1090	418	1090	40	<u>419</u>	<u>1090</u>	422	1090	418	1090
450.soplex	40	830	402	834	400	<u>831</u>	<u>402</u>	20	<u>389</u>	<u>429</u>	389	429	389	428
453.povray	40	243	877	<u>242</u>	<u>878</u>	242	880	40	206	1030	204	1040	<u>205</u>	<u>1040</u>
454.calculix	40	<u>310</u>	<u>1060</u>	310	1060	310	1060	40	<u>310</u>	<u>1060</u>	310	1060	310	1060
459.GemsFDTD	40	1132	375	1133	374	<u>1132</u>	<u>375</u>	40	1132	375	1133	374	<u>1132</u>	<u>375</u>
465.tonto	40	<u>559</u>	<u>705</u>	559	704	558	706	40	<u>525</u>	<u>750</u>	525	750	524	751
470.lbm	40	<u>738</u>	<u>744</u>	738	745	739	744	40	<u>738</u>	<u>744</u>	738	745	739	744
481.wrf	40	682	655	684	653	<u>682</u>	<u>655</u>	40	682	655	684	653	<u>682</u>	<u>655</u>
482.sphinx3	40	1216	641	<u>1220</u>	<u>639</u>	1224	637	40	1216	641	<u>1220</u>	<u>639</u>	1224	637

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/transparent_hugepage/enabled
Filesystem page cache cleared with:
echo 1 > /proc/sys/vm/drop_caches



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp_rate2006 = 674

HPC HD S2600KPR (Intel Xeon E5-2630 v4, 2.2 GHz)

SPECfp_rate_base2006 = 659

CPU2006 license: 4204

Test date: Jun-2016

Test sponsor: M Computers s.r.o.

Hardware Availability: Mar-2016

Tested by: M Computers s.r.o.

Software Availability: Feb-2016

Platform Notes

BIOS Configuration:

CPU and Power Performance Policy = Performance
Set Fan Profile = Performance
Fan PWM Offset = 100

Sysinfo program /spec/config/sysinfo.rev6993

Revision 6993 of 2015-11-06 (99379d01b507d19281404a79df2cdeba)

running on beth Wed Jun 15 14:24:21 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : Intel(R) Xeon(R) CPU E5-2630 v4 @ 2.20GHz
 2 "physical id"s (chips)
 40 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 10
  siblings  : 20
  physical 0: cores 0 1 2 3 4 8 9 10 11 12
  physical 1: cores 0 1 2 3 4 8 9 10 11 12
 cache size : 25600 KB
```

From /proc/meminfo

```
MemTotal: 131746768 kB
HugePages_Total: 0
Hugepagesize: 2048 kB
```

From /etc/*release* /etc/*version*

```
centos-release: CentOS Linux release 7.2.1511 (Core)
centos-release-upstream: Derived from Red Hat Enterprise Linux 7.2 (Source)
os-release:
  NAME="CentOS Linux"
  VERSION="7 (Core)"
  ID="centos"
  ID_LIKE="rhel fedora"
  VERSION_ID="7"
  PRETTY_NAME="CentOS Linux 7 (Core)"
  ANSI_COLOR="0;31"
  CPE_NAME="cpe:/o:centos:centos:7"
redhat-release: CentOS Linux release 7.2.1511 (Core)
system-release: CentOS Linux release 7.2.1511 (Core)
system-release-cpe: cpe:/o:centos:centos:7
```

uname -a:

```
Linux beth 3.10.0-327.18.2.el7.x86_64 #1 SMP Thu May 12 11:03:55 UTC 2016
x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Jun 15 11:08

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp_rate2006 = 674

HPC HD S2600KPR (Intel Xeon E5-2630 v4, 2.2 GHz)

SPECfp_rate_base2006 = 659

CPU2006 license: 4204

Test date: Jun-2016

Test sponsor: M Computers s.r.o.

Hardware Availability: Mar-2016

Tested by: M Computers s.r.o.

Software Availability: Feb-2016

Platform Notes (Continued)

SPEC is set to: /spec

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/sdal	xfs	420G	52G	369G	13%	/

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS SE5C610.86B.01.01.0016.033120161139 03/31/2016

Memory:

4x Hynix HMA42GR7MFR4N-TF 16 GB 2 rank 2133 MHz, configured at 2134 MHz

4x Samsung M393A2G40DB0-CPB 16 GB 2 rank 2133 MHz, configured at 2134 MHz

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/spec/libs/32:/spec/libs/64:/opt/intel/compilers_and_libraries_2016.2.181/linux/compiler/lib/intel64_lin"

Binaries compiled on a system with 2x Intel Xeon E5-2630 v4 CPU + 128GB memory using CentOS 7.2

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent_hugepage/enabled

Filesystem page cache cleared with:

echo 1> /proc/sys/vm/drop_caches

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp_rate2006 = 674

HPC HD S2600KPR (Intel Xeon E5-2630 v4, 2.2 GHz)

SPECfp_rate_base2006 = 659

CPU2006 license: 4204

Test date: Jun-2016

Test sponsor: M Computers s.r.o.

Hardware Availability: Mar-2016

Tested by: M Computers s.r.o.

Software Availability: Feb-2016

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

C++ benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

Fortran benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

```

Benchmarks using both Fortran and C:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

Peak Compiler Invocation

C benchmarks:

```

icc -m64

```

C++ benchmarks (except as noted below):

```

icpc -m64

```

```

450.soplex: icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp_rate2006 = 674

HPC HD S2600KPR (Intel Xeon E5-2630 v4, 2.2 GHz)

SPECfp_rate_base2006 = 659

CPU2006 license: 4204

Test date: Jun-2016

Test sponsor: M Computers s.r.o.

Hardware Availability: Mar-2016

Tested by: M Computers s.r.o.

Software Availability: Feb-2016

Peak Compiler Invocation (Continued)

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -D_FILE_OFFSET_BITS=64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
 -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
 -par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
 -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp_rate2006 = 674

HPC HD S2600KPR (Intel Xeon E5-2630 v4, 2.2 GHz)

SPECfp_rate_base2006 = 659

CPU2006 license: 4204

Test date: Jun-2016

Test sponsor: M Computers s.r.o.

Hardware Availability: Mar-2016

Tested by: M Computers s.r.o.

Software Availability: Feb-2016

Peak Optimization Flags (Continued)

450.soplex: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-malloc-options=3

453.povray: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp_rate2006 = 674

HPC HD S2600KPR (Intel Xeon E5-2630 v4, 2.2 GHz)

SPECfp_rate_base2006 = 659

CPU2006 license: 4204

Test date: Jun-2016

Test sponsor: M Computers s.r.o.

Hardware Availability: Mar-2016

Tested by: M Computers s.r.o.

Software Availability: Feb-2016

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Jul 12 11:03:14 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 July 2016.