



# SPEC® CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation


## Fujitsu Fujitsu SPARC M12-2S

SPECint®\_rate2006 = 3790

SPECint\_rate\_base2006 = 3270

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Mar-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017



### Hardware

CPU Name: SPARC64 XII  
 CPU Characteristics: High Speed Mode up to 4.35 GHz  
 CPU MHz: 4250  
 FPU: Integrated  
 CPU(s) enabled: 48 cores, 4 chips, 12 cores/chip, 8 threads/core  
 CPU(s) orderable: 1 to 16 BBs; each BB contains 1 or 2 CPU chips; the number of orderable total cores is 2, 3, 4, .. 384  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 512 KB I+D on chip per core  
 L3 Cache: 32 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 2 TB (64 x 32 GB 2Rx4 PC4-2400T-R)  
 Disk Subsystem: 1 x 600 GB 10K RPM SAS (for system disk)  
 Other Hardware: None

### Software

Operating System: Oracle Solaris 11.3 (with June 2017 SRU)  
 Compiler: C/C++: Version 12.6 of Oracle Developer Studio  
 Auto Parallel: No  
 File System: tmpfs  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: None



# SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2S

SPECint\_rate2006 = 3790

SPECint\_rate\_base2006 = 3270

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Mar-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	384	1346	2790	<b><u>1344</u></b>	<b><u>2790</u></b>	1344	2790	384	953	3940	<b><u>951</u></b>	<b><u>3940</u></b>	951	3950
401.bzip2	384	2302	1610	2300	1610	<b><u>2300</u></b>	<b><u>1610</u></b>	192	1084	1710	1082	1710	<b><u>1084</u></b>	<b><u>1710</u></b>
403.gcc	384	1212	2550	<b><u>1213</u></b>	<b><u>2550</u></b>	1229	2510	384	1196	2580	1175	2630	<b><u>1194</u></b>	<b><u>2590</u></b>
429.mcf	384	1260	2780	1265	2770	<b><u>1264</u></b>	<b><u>2770</u></b>	192	400	4380	<b><u>401</u></b>	<b><u>4370</u></b>	401	4370
445.gobmk	384	<b><u>1258</u></b>	<b><u>3200</u></b>	1261	3190	1255	3210	384	1108	3640	<b><u>1107</u></b>	<b><u>3640</u></b>	1107	3640
456.hammer	384	909	3940	<b><u>910</u></b>	<b><u>3940</u></b>	910	3940	192	413	4340	<b><u>413</u></b>	<b><u>4330</u></b>	415	4320
458.sjeng	384	<b><u>1649</u></b>	<b><u>2820</u></b>	1652	2810	1647	2820	384	<b><u>1444</u></b>	<b><u>3220</u></b>	1446	3210	1439	3230
462.libquantum	384	<b><u>283</u></b>	<b><u>28100</u></b>	283	28100	283	28100	96	<b><u>50.3</u></b>	<b><u>39500</u></b>	50.4	39500	50.3	39600
464.h264ref	384	2040	4170	<b><u>2040</u></b>	<b><u>4160</u></b>	2042	4160	192	930	4570	<b><u>933</u></b>	<b><u>4560</u></b>	934	4550
471.omnetpp	384	1473	1630	1473	1630	<b><u>1473</u></b>	<b><u>1630</u></b>	384	1418	1690	<b><u>1417</u></b>	<b><u>1690</u></b>	1417	1690
473.astar	384	<b><u>1341</u></b>	<b><u>2010</u></b>	1341	2010	1341	2010	384	1307	2060	<b><u>1307</u></b>	<b><u>2060</u></b>	1307	2060
483.xalancbmk	384	<b><u>780</u></b>	<b><u>3400</u></b>	780	3400	779	3400	384	727	3640	727	3650	<b><u>727</u></b>	<b><u>3650</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

Processes were assigned to specific processors using 'pbind' commands. The config file option 'submit' was used, along with a list of processors in the 'BIND' variable, to generate the pbind commands. (For details, please see the config file.)

## Operating System Notes

### Shell Environments:

ulimit -s 131072 was used to limit the space consumed by the stack (and therefore make more space available to the heap).

The "Logical Domains Manager" service was turned off using the command "svcadm disable ldmd".

### System Tunables:

(/etc/system parameters)

autoup = 86400

Causes pages older than the listed number of seconds to be written by fsflush.  
doiflush = 0

Controls whether file system metadata syncs will be executed during fsflush invocations.  
dopageflush = 0

Controls whether memory is examined for modified pages during fsflush invocations.  
zfs:zfs\_arc\_max=1073741824

Determines the maximum size of the ZFS Adaptive Replacement Cache (ARC).



# SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2S

SPECint\_rate2006 = 3790

SPECint\_rate\_base2006 = 3270

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Mar-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Platform Notes

Firmware Settings:  
(XSCF operations)  
Set High Speed Mode via XSCF command "sethsmode -s on".

Sysinfo program /export/cpu2006/config/sysinfo  
Revision 6993 of 2015-11-06 (c9426fd40261140bb4c02f7d35768596)  
running on H2S-254-D0 Tue Mar 21 07:02:25 2017

This section contains SUT (System Under Test) info as seen by  
some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /usr/sbin/psrinfo
SPARC64-XII (chipid 0, clock 4250 MHz)
SPARC64-XII (chipid 1, clock 4250 MHz)
SPARC64-XII (chipid 2, clock 4250 MHz)
SPARC64-XII (chipid 3, clock 4250 MHz)
4 chips
384 threads
4250 MHz
```

From kstat: 48 cores

From prtconf: 2093056 Megabytes

```
/etc/release:
Oracle Solaris 11.3 SPARC
uname -a:
SunOS H2S-254-D0 5.11 11.3 sun4v sparc sun4v
```

SPEC is set to: /export/cpu2006

```
disk: df -h /export/cpu2006
Filesystem      Size  Used  Available Capacity  Mounted on
rpool/export    547G  44G      218G      17%    /export
```

(End of data from sysinfo program)

## General Notes

The Building Block (BB) is just a Fujitsu SPARC M12-2S that is the basic unit to be expanded as if stacking up children's blocks.

File System:  
tmpfs: output\_root was used to put run directories in /tmp/cpu2006  
zfs: operating system

SPEC CPU2006 benchmark:  
Updated with runspec --update



# SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2S

SPECint\_rate2006 = 3790

SPECint\_rate\_base2006 = 3270

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Mar-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Base Compiler Invocation

C benchmarks:  
cc  
  
C++ benchmarks:  
CC

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_SOLARIS\_SPARC  
403.gcc: -DSPEC\_CPU\_SOLARIS  
462.libquantum: -DSPEC\_CPU\_SOLARIS  
483.xalancbmk: -DSPEC\_CPU\_SOLARIS

## Base Optimization Flags

C benchmarks:  
-std=c99 -m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M  
-xsegment\_align=4M -xthroughput -xalias\_level=std  
  
C++ benchmarks:  
-m32 -fast -xtarget=sparc64xii -xipo=2 -xpagesize=4M  
-xsegment\_align=4M -xthroughput -xalias\_level=compatible  
-library=stlport4 -lfast

## Base Other Flags

C benchmarks:  
-xjobs=8  
  
C++ benchmarks:  
-xjobs=8

## Peak Compiler Invocation

C benchmarks:  
cc  
  
C++ benchmarks:  
CC



# SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2S

SPECint\_rate2006 = 3790

SPECint\_rate\_base2006 = 3270

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Mar-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_SOLARIS\_SPARC  
403.gcc: -DSPEC\_CPU\_SOLARIS  
462.libquantum: -DSPEC\_CPU\_SOLARIS  
483.xalancbmk: -DSPEC\_CPU\_SOLARIS

## Peak Optimization Flags

C benchmarks:

400.perlbench: -std=c99 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xtarget=sparc64xplus -xipo=1  
-xalias\_level=std -xrestrict -xprefetch=no%auto -xO4  
-Wc,-Qiselect-funcalign=4 -xthroughput=no -lfast

401.bzip2: -std=c99 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xalias\_level=strong -xprefetch=no%auto  
-Wc,-Qiselect-funcalign=4 -Wc,-Qicache-chbab=1  
-xinline\_param=max\_inst\_hard:1000,max\_inst\_soft:500,max\_growth:60  
-lfast

403.gcc: -std=c99 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xO4 -xipo=2 -xprefetch=no%auto  
-Wc,-Qiselect-funcalign=64  
-xcache=32/128/4/4:256/128/8/4:8192/128/16/24  
-xalias\_level=layout

429.mcf: -std=c99 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xipo=2 -xalias\_level=std -xprefetch=latx:0.2  
-W2,-Asac -Wc,-Qiselect-funcalign=64

445.gobmk: -std=c99 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xO4 -xalias\_level=std -xrestrict  
-xprefetch=no%auto -Wc,-Qiselect-funcalign=64  
-Wc,-Qgsched-T=4

456.hmmer: -std=c99 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xipo=1 -xunroll=8 -Wc,-Qms\_pipe-pref

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2S

SPECint\_rate2006 = 3790

SPECint\_rate\_base2006 = 3270

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Mar-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Peak Optimization Flags (Continued)

456.hmmmer (continued):

-Wc,-Qiselect-funcalign=4  
-xcache=32/128/4/4:256/128/8/4:8192/128/16/48

458.sjeng: -std=c99 -xprofile=collect:./feedback(pass 1)

-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xO4 -xipo=2 -xalias\_level=std -xunroll=4  
-Wc,-Qiselect-funcalign=4 -W2,-Afully\_unroll:always=on  
-xprefetch=latx:0.6 -xcheck=%none

462.libquantum: -std=c99 -m32 -fast -xtarget=sparc64xii -xpagesize=256M

-xsegment\_align=256M -xthroughput -m64  
-xtarget=sparc64xplus -xipo=2  
-xcache=32/128/4/4:256/128/8/4:8192/128/16/24  
-xinline\_param=level:1 -Wc,-Qiselect-funcalign=4  
-xalias\_level=layout -xprefetch=latx:0.2

464.h264ref: -std=c99 -xprofile=collect:./feedback(pass 1)

-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xtarget=sparc64xplus -xipo=1  
-Wc,-Qiselect-funcalign=4 -xthroughput=no  
-xalias\_level=layout -xprefetch=latx:0.2 -xcheck=%none

C++ benchmarks:

471.omnetpp: -xprofile=collect:./feedback(pass 1)

-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xipo=1 -xalias\_level=compatible -xunroll=2  
-xprefetch\_level=3 -W2,-Asac -xthroughput=no -lfast

473.astar: -xprofile=collect:./feedback(pass 1)

-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xtarget=sparc64xplus -xalias\_level=compatible  
-xipo=2 -xunroll=6 -xrestrict=%source  
-Wc,-Qiselect-funcalign=64 -Wc,-Qgsched-T=4  
-xprefetch=latx:0.3 -lfast

483.xalancbmk: -xprofile=collect:./feedback(pass 1)

-xprofile=use:./feedback(pass 2) -m32 -fast  
-xtarget=sparc64xii -xpagesize=256M -xsegment\_align=256M  
-xthroughput -xipo=2 -xalias\_level=compatible -xdepend  
-xprefetch\_level=3 -xprefetch=latx:0.4 -library=stlport4  
-W2,-Asac -Wc,-Qiselect-funcalign=64 -features=no%except  
-lfast



# SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC M12-2S

SPECint\_rate2006 = 3790

SPECint\_rate\_base2006 = 3270

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Mar-2017  
Hardware Availability: Apr-2017  
Software Availability: Jul-2017

## Peak Other Flags

C benchmarks:  
-xjobs=8

C++ benchmarks:  
-xjobs=8

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Oracle-Developer-Studio12.6.html>  
<http://www.spec.org/cpu2006/flags/Fujitsu-M12-2S.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Oracle-Developer-Studio12.6.xml>  
<http://www.spec.org/cpu2006/flags/Fujitsu-M12-2S.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Apr 20 09:42:29 2017 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 19 April 2017.