SPECweb96 Result

©Copyright 1996, Standards Performance Evaluation Corporation

Hewlett-Packard
HP 9000 Model K460

SPECweb96= 1827

Test Date : Nov-96

Tested by : HP Cupertino, CA

Hardware Avail:	Sep-96	OS Avail:	Feb-97	HTTP Software Avail:	Nov-96	SPEC license #:	3

Throughput ops/sec	Response msec
185	6.7
372	11.0
557	19.7
743	33.0
930	41.6
1115	44.4
1300	41.5
1485	48.1
1671	52.3
1827	102.6



Hardware

Model Name:	HP 9000 Model K460
Processor:	PA8000 180MHz
# of Processors:	4
Primary Cache:	1MBI+1MBD off chip
Secondary Cache:	None
Other Cache:	None
Memory:	2GB
Disk Subsystem:	3 HPC2247WD SCSI Drives
Disk Controllers:	1 internal FWD SCSI
Other Hardware:	Fore ASX-200WG ATM switch

Software

Operating System:	HP-UX 10.20
File System:	HFS
Other Software:	PHNE_9107, PHNE_9182

HTTP Software

Vendor:	Zeus Technology Limited
HTTP Software:	Zeus 1.1.4
# of "threads":	4
Server Cache:	zeus -t 9000 -l 250 -b 1048576 -q
Log Mode:	Common Log Format

Network

# of Controllers:	3
Network Controllers:	HP J2803B opt 001, 155Mbit OC3c ATM
# of Nets:	3
Type of Nets:	ATM OC3c
Network Speed:	155Mbit
Time Wait (secs):	60 (Non RFC1122)

Load Generators

# of Load Generators:	9
# of Processes Each:	40
Model:	4@HP9000/C110; 5@HP9000/B160L
Processor:	4@120MHz PA7200; 5@160MHz PA7300LC
# of CPUs:	1
Memory:	128Mbyte
OS:	HPUX 10.20
Compiler:	HP92453-01 A.10.32.03 HP C Compiler

Benchmark Configuration

Max Requested Load:	1855
Max Fileset Size (MB):	942

Notes/Tuning Information

```
dbc_max_pct 5, ninode 16000, adb tcphash_size 16384
workload data files permissions set to 0755
chatr +pi L Zeus executable
Zeus processes bound to processors (via mpcntl)
```

For More Information contact

SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 22110

(703) 331-0180
info@specbench.org
http://www.specbench.org/