SPECweb99_SSL Result

```
================================================================================
                                                    ||
 IBM : eServer xSeries 345                          ||      CD SPECweb99_SSL
 Zeus : Zeus V4.2                                   ||
                                                    ||
================================================================================
    SPEC has discovered a code defect in the SPECweb99_SSL test harness run on
    the client systems used in this result.  The defect prevents these client
    systems from generating the correct SPECweb99_SSL workload.  Specifically,
    the defect in the SPECweb99_SSL code results in the clients not generating
    any of the required SSL ClientKeyExchanges during the benchmark.  Therefore,
    the results presented here are not comparable with any other SPECweb99_SSL
    results.
================================================================================
```

PERFORMANCE

| Iteration | Conforming Simultaneous Connections |
|---|---|
| 1 | CD |
| 2 | CD |
| 3 | CD |
| Median | CD |

| | Availability Dates |
|---|---|
| All Hardware | Feb-2003 |
| HTTPS Software | Nov-2002 |
| Operating System | Jul-2002 |
| Supplemental System | May-2002 |

| | Hardware |
|---|---|
| Vendor | IBM |
| Model | eServer xSeries 345 |
| Processor | 2.8B GHz Intel Xeon |
| # Processors | 2 cores, 2 chips, 1 core/chip |
| Primary Cache | 12KBI+8KBD on chip |
| Secondary Cache | 512KB |
| Other Cache | None |
| Memory | 4 GB |
| Disk Subsystem | 6 36GB 15KRPM Ultra 320 SCSI Drives |
| Disk Controllers | 1 LSI 1030 Ultra 320 SCSI LOM |
| Other Hardware | 1 Extreme Networks Summit 7i GbE Switch |

| | Software |
|---|---|
| Operating System | Red Hat Linux 7.3 |
| File System | ext2 |
| Other Software | None |

| | HTTPS Software |
|---|---|
| Vendor | Zeus |
| HTTPS Software | Zeus V4.2 |
| API | Zeus PEPP 0.8 ISAPI used for Dynamic content |
| Server Cache | None |
| Log Mode | Zeus CLF |

| | Test Sponsor |
|---|---|
| Test Date | Feb-2003 |
| Tested By | IBM |
| SPEC License | 11 |

| | Network |
|---|---|
| # of Controllers | 1 |
| Network Controllers | Integrated Gigabit Ethernet |
| # of Nets | 1 |
| Type of Nets | Gigabit Ethernet |
| Network Speed | 1 Gb/s |
| MSL (sec) | 30 (Non RFC1122) |
| Time-Wait (sec) | 60 (Non RFC1122) |
| MTU | 1500 |

| | Clients |
|---|---|
| # of Clients | 8 |
| Model | IBM eServer xSeries 330 |
| Processor | 933Mhz Pentium III |
| # of Processors | 1 |
| Memory | 256MB |
| Network Controller | IBM Netfinity Gigabit Ethernet Adapter |
| Operating System | Microsoft Windows 2000 Professional w/SP3 |
| Compiler | Microsoft VC++ v6.0 |

Benchmark Configuration

Requested Connections 1150
Fileset Size (MB) 3801.52

==========

Notes/Tuning information

SUT Notes
1 disk for OS
6 disk software RAID0, using 64KB chunk size, for web pages and logs

Operating System Notes
Tuning parameters:
- net.ipv4.ip_forward=0, default 0
- net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
- net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
- net.ipv4.tcp_max_tw_buckets = 200000, sets TCP time-wait buckets pool size, default 180000
- net.core.rmem_max = 10000000, maximum receive socket buffer size, default 65535
- net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
- net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
- net.core.wmem_default = 10000000, default send socket buffer size, default 65535
- net.core.optmem_max = 10000000, default 10240
- net.core.hot_list_length = 10000, maximum number of skb-heads to be cached, default 128
" - net.core.netdev.max_backlog = 20000, default 300
- net.ipv4.tcp_rmem = 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
- net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
- net.ipv4.tcp_mem=30000000 30000000 30000000, maximum TCP buffer space, default 31744 32256 32768
Kernel is standard default Red Hat Linux (2.4.18-3bigmem)

HTTPS Software Notes
Zeus Configuration
- tuning!num_children 4
- tuning!so_wbuff_size 1048576
- tuning!softservers no
- tuning!cbuff_size 65536
- tuning!clientfirst_optimise yes
- tuning!ssl_sessioncache_size 4951
- tuning!sendfile yes
- tuning!sendfile_minsize 1
- tuning!listen_queue_size 8192
- tuning!so_rbuff_size 0
- tuning!modules!cgi!cleansize 0
- tuning!timeout 600
- tuning!keepalive_timeout 20
- tuning!keepalive_max 3300
- tuning!maxaccept 64
See IBM-Zeus-tuning-20021224.txt for a description of the Zeus tuning parameters
ISAPI Source code is available in the SPECweb99_SSL support docs as HP-20020724-API.tar.gz

==========

Test Run Details

| | Run Num | Conforming Connections | Percent Conform | Throughput ops/sec | Response msec | ops/sec/ loadgen | Kbits/ sec |
|---|---|---|---|---|---|---|---|
| => | 1 | CD | CD | CD | CD | CD | CD |
| | 2 | CD | CD | CD | CD | CD | CD |
| | 3 | CD | CD | CD | CD | CD | CD |